



31952 – F55BX/835

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



Bulb



Base

[View Larger](#)**GENERAL CHARACTERISTICS**

Lamp type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Wattage	55
Voltage	101
Rated Life	10000 hrs
Starting Temperature (MIN)	10 °C (50 °F)
LEED-EB MR Credit	98 picograms Hg per mean lumen hour
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

ADDITIONAL RESOURCES[Catalogs](#)[Testimonials](#)[Disposal Policies & Recycling Information](#)**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens	4800
Mean Lumens	4080
Nominal Initial Lumens per Watt	87
Color Temperature	3500 K
Color Rendering Index (CRI)	82

ELECTRICAL CHARACTERISTICS

Lamp Current	0.550 A
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	20.7000 in (525.7 mm)
Nominal Length	20.700 in (525.7 mm)

PRODUCT INFORMATION

Product Code	31952
Description	F55BX/835
ANSI Code	60901-IEC-6255-2
Standard Package	Case
Standard Package GTIN	10043168319529
Standard Package Quantity	25
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	25
UPC	043168319522

COMPATIBLE GE BALLASTS

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
47542	B254PUNV-DGE1C	1	99.0	1.12
47506	C242UNVBES-IP	1	99.0	0.83
47509	C2421INVSE-IP	1	99.0	0.83