

Fast Warm-Up, Plug-In CFL Triple Biax[®] Lamps

**GE provides faster warm-up times
on the fast growing, very popular line of
4-pin plug-in CFL Triple Biax[®] Lamps**

50% faster warm up

GE's new 4-pin plug-in Triple Biax lamps warm up to full brightness 50% faster and provide immediate flicker-free light.

Outstanding energy efficiencies

As much as 77% energy cost savings vs. incandescent lamps. The 42-watt delivers 3200 lumens, 12% more than a standard 150-watt incandescent bulb!

TCLP Compliant

All GE 4-pin plug-in Triple Biax lamps feature low mercury and are TCLP compliant in both the U.S. and Canada.

Long Life – 12,000 hours

GE Biax Lamps last up to 16 times longer than standard incandescent bulbs. Longer life means lower lamp replacement and maintenance costs.

Excellent Color – 82 CRI

GE's SPX color provides excellent color rendering. Available in a choice of color temperatures: 2700K, 300K, 3500K and 4100K.

Dimmable

GE 4-pin plug-in Triple Biax lamps can be operated on dimming circuits for greater application and design flexibility.



**GE – bringing incandescent
features to compact
fluorescent lamps**



**GE - Innovative,
Energy-Saving Lighting**



imagination at work

Fast Warm-Up, Plug-In CFL Triple Biax® Lamps

Watts	Color Temperature	Lamp Description	P/C	Initial Lumens	CRI	Rated Life	TCLP Compliant
13	2700K	F13TBX/SPX27/A/4P	34391	900	82	12,000	Yes
	3000K	F13TBX/SPX30/A/4P	34395	900	82	12,000	Yes
	3500K	F13TBX/SPX35/A/4P	34400	900	82	12,000	Yes
	4100K	F13TBX/SPX41/A/4P	34387	900	82	12,000	Yes
18	2700K	F18TBX/SPX27/A/4P	34392	1200	82	12,000	Yes
	3000K	F18TBX/SPX30/A/4P	34396	1200	82	12,000	Yes
	3500K	F18TBX/SPX35/A/4P	34405	1200	82	12,000	Yes
	4100K	F18TBX/SPX41/A/4P	34385	1200	82	12,000	Yes
26	2700K	F26TBX/SPX27/A/4P	34393	1710	82	12,000	Yes
	3000K	F26TBX/SPX30/A/4P	34397	1710	82	12,000	Yes
	3500K	F26T8X/SPX3S/A/4P	34406	1710	82	12,000	Yes
	4100K	F26TBX/SPX41/A/4P	34381	1710	82	12,000	Yes
32	2700K	F32TBX/SPX27/A/4P	39377	2200	82	12,000	Yes
	3000K	F32TBX/SPX30/A/4P	39378	2200	82	12,000	Yes
	3500K	F32TBX/SPX35/A/4P	39379	2200	82	12,000	Yes
	4100K	F32TBX/SPX41/A/4P	39380	2200	82	12,000	Yes
42	2700K	F42TBX/827/A/4P/EOL	46312	3200	82	12,000	Yes
	3000K	F42TBX/830/A/4P/EOL	46313	3200	82	12,000	Yes
	3500K	F42TBX/835/A/4P/EOL	46314	3200	82	12,000	Yes
	4100K	F42TBX/841/A/4P/EOL	46315	3200	82	12,000	Yes

Nominal Lamp Dimension - Inches (mm)

Lamp Type	A	B	C	D	E
F13TBX/08	4.25 (108)	2.60 (66)	.80 (19)	1.93 (49)	.59 (15)
F18TBX/23	4.84 (123)	3.19 (81)	.80 (19)	1.93 (49)	.59 (15)
F26TBX/33	5.24 (133)	3.58 (91)	.80 (19)	1.93 (49)	.59 (15)
F32TBX/48	5.83 (148)	4.17 (106)	.80 (19)	1.93 (49)	.59 (15)
F42TBX/54	6.06 (154)	4.37 (111)	.79 (20)	2.28 (58)	.59 (15)



For additional product and application information, please consult GE's Website:
www.gelighting.com

