

48863 - F57QBX835A4P/EOL

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

• Super long life









CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-

Bulb T4
Base GX24-q5
Equivalent Wattage (NOM) 200.0 W
Rated Life (NOM) 17000.0 h
Starting Temperature (MIN) -20.0 °C
Mercury Content (NOM) 3.0 mg
Picograms of Mercury (NOM) 47.69475 g

Picograms of Mercury (NOM) 47.69475 pg Additional Info Dimmable with appropriate

dimming ballast./End of Life Protection (EOL)/TCLP

compliant

Primary Application Facilities; Retail

Display; Hospitality; Office; Restaurant; W.

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM) 4300.0 Mean Lumens (NOM) 3700.0 Nominal Initial Lumens per Watt 75.4386

(NOM)

Color Temperature (NOM) 3500.0 K Color Rendering Index (CRI) 82.0

(NOM)

ELECTRICAL CHARACTERISTICS

 Wattage (NOM)
 57.0

 Voltage (NOM)
 120.0

 Lamp Current (NOM)
 0.32 A

 Current Crest Factor (MAX)
 1.7

 Supply Current Frequency
 20.0 Hz

(NOM)

DIMENSIONS

Maximum Overall Length 7.100 in(180.3 mm)

(MOL) (NOM)

Nominal Length (NOM) 7.100 in(180.3 mm)

PRODUCT INFORMATION

Product Code 48863

 Description
 F57QBX835A4P/EOL

 ANSI Code
 60901-IEC-7457-1

Standard Package Case

Standard Package GTIN 10043168488638

Standard Package Quantity

Sales Unit

No Of Items Per Sales Unit

No Of Items Per Standard

10

Package

UPC 043168488631

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life