



## WORLDWIDE PARTNER

Commercial Products & Solutions

SITE SEARCH > HOME \*\* PRODUCTS > EDUCATION / RESOURCES > LIGHTING APPLICATIONS

Where to Buy | FAQs | Contact Us | EliteNet

<u>Products</u> > 97571

# 97571 - F13BX/841/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse





Lamp type	Compact Fluorescent - Plug-In
Bulb	T4
Base	GX23
Wattage	13
Voltage	120/59
Rated Life	10000 hrs
Starting Temperature (MIN)	0 ℃ (32 뚜)
LEED-EB MR Credit	563 picograms Hg per mean lumen hour
Additional Info	TCLP compliant
Primary Application	Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

PHOTOMETRIC CHARACTERISTICS		
Initial Lumens	825	
Mean Lumens	710	
Nominal Initial Lumens per Watt	63	
Color Temperature	4100 K	
Color Rendering Index (CRI)	82	

Lamp Current	0.285 A
Current Crest Factor (MAX)	1.7
Supply Current Frequency	60 Hz

Maximum Overall Length (MOL)	7.3000 in (185.4 mm)
Nominal Length	7.000 in (177.8 mm)
Base Face to Top of Lamp	6.690 in (169.9 mm)

PRODUCT INFORMATION		
Product Code	97571	
Description	F13BX/841/ECO	



ADDITIONAL RESOURCES	
Catalogs	
<u>Testimonials</u>	
<b>Disposal Policies &amp; Recycling Information</b>	

ANSI Code	60901-IEC-0013-1
Standard Package	BUNDLE
Standard Package Quantity	100
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	100
UPC	043168975711

## **COMPATIBLE GE BALLASTS**

Product Code	Description	# of Bulbs	Power Factor	Ballast Factor
87533	GEM1CF13PH120	1	50.0	0.9
87655	GEM2CF13PH277	2	95.0	0.9

# **A** CAUTIONS & WARNINGS

See list of cautions & warnings.

## **NOTES**

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map
Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use
Copyright General Electric Company 1997-2009