| WORLDWIDE PARTI | NER | | | | Com | mercial Products & Solutions |
|-----------------------------------------------|----------------------------------|--------------------|--------------------------|------------------------------|----------|-----------------------------------|
| SITE | E SEARCH | > HOME | * PRODUCTS | EDUCATION / RESOURCE | S | » LIGHTING APPLICATIONS |
| | | | | | | Buy FAQs Contact Us EliteNe |
| Products > 97607 | | | | | | <u> </u> |
| <u>-100ucis</u> > 97607 | | | | | | |
| 97607 – F26DBX/ GE Ecolux® Biax® T4 | | etail Display; Hos | spitality; Office; Resta | urant; Warehouse | | |
| High Color Rendering Energy Savings | | | _ | | | |
| GENERAL CHARACT | TERISTICS | | | | | |
| Lamp type | | orescent - Plug- | In | | | |
| Bulb | T4 | | | 15. | | |
| Base | G24d-3 | | | 66 | | |
| Wattage | 26 | | | | | |
| Voltage | 105 | | | Bulb | Base | |
| Rated Life | 10000 hrs | | | [] | 6 | 3 |
| Starting Temperature MIN) | -9 ℃ (16 ℉) | | | | | |
| Cathode Resistance | 2.700 Ohm | | | 77 | | 1 |
| _EED-EB MR Credit | 274 picogran lumen hour | ns Hg per mean | | | View La | arger |
| Additional Info | TCLP compli | ant | | 2500112050 | | |
| Primary Application | Hospitality; Office; Restaurant; | | | RESOURCES | | |
| | Warehouse | | Testimonials | | | |
| PHOTOMETRIC CHA | RACTERISTIC | s | | cies & Recycling Information | <u>l</u> | |
| Initial Lumens | 1710 | | | | | |
| Mean Lumens | 1460 | | | | | |
| Nominal Initial Lumens per Watt | 65 | | | | | |
| Color Temperature | 3000 K | | | | | |
| Color Rendering Index (CRI) | 82 | | | | | |
| ELECTRICAL CHARA | ACTERISTICS | | | | | |
| Open Circuit Voltage Across Starter (MIN) | 198 V | | | | | |
| Lamp Current | 0.325 A | | | | | |
| Current Crest Factor (MAX) | 1.7 | | | | | |
| Supply Current Frequency | 60 Hz | | | | | |
| DIMENSIONS | | | | | | |
| Maximum Overall Length (MOL) | 6.6700 in (16 | 69.4 mm) | | | | |
| | C 700 in (470 | 1 mm) | | | | |
| Nominal Length | 6.700 in (170 |). [[[[[[]]] | | | | |

PRODUCT INFORMATION

| Product Code | 97607 | | | |
|-------------------------------------|------------------|--|--|--|
| Description | F26DBX/830/ECO | | | |
| ANSI Code | 60901-IEC-0526-2 | | | |
| Standard Package | BUNDLE | | | |
| Standard Package Quantity | 50 | | | |
| Sales Unit | Unit | | | |
| No Of Items Per Sales Unit | 1 | | | |
| No Of Items Per Standard Package | 50 | | | |
| UPC | 043168976077 | | | |

COMPATIBLE GE BALLASTS

| Product | Description | # of | Power | Ballast |
|---------|---------------|-------|--------|---------|
| Code | | Bulbs | Factor | Factor |
| 87700 | GEM2CF24PH277 | 2 | 97.0 | 0.9 |

A CAUTIONS & WARNINGS

See list of cautions & warnings.

NOTES

• Based on 60Hz reference circuit.

• Fluorescent lamp lumens decline during life

Return To Top

Home | Products | EliteNet | Education/Resources | Lighting Applications | Where to Buy | FAQs | Contact Us | Site Map Products for Your Home | Press Room | Corporate | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright General Electric Company 1997-2009