



ProLume®
◀ Plug-Ins

COMPACTS

ProLume® Plug-Ins

Halco
LIGHTING TECHNOLOGIES®

Energy Efficient

- Save up to 80% in energy costs compared to standard incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI

Technical Data

- Operating temperature 0 - 140°F
- Lead-free glass
- End-of-Life protection

Broad Assortment

- Single and Double Tube 2-Pin
- Single, Double, Triple and Spiral Tube 4-Pin
- Flat Quad 4-Pin
- 2700, 3500, 4100 and 5000K

Long Life

- 12,000 Hours Average Rated Life
- 1-Year Guarantee

Benefits

- Saves energy
- Low maintenance
- Excellent color rendering
- TCLP compliant

Applications

- Wall sconces
- Down lighting
- Task lighting
- Security

The **Eco-Shield®** mark indicates this product is **TCLP compliant**.



Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.

ISO 9001 Certified



**where there's light,
there's halco®**

(800) 677-3334
halcolighting.com

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Avg Rated Life	MOL (Inches)
SINGLE TUBE 2-PIN											
T4	5	G-23	109100	PL5S/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	250	12000	4.3"
T4	5	G-23	109102	PL5S/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	250	12000	4.3"
T4	7	G-23	109106	PL7S/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	400	12000	5.4"
T4	7	G-23	109107	PL7S/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	400	12000	5.4"
T4	7	G-23	109108	PL7S/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	400	12000	5.4"
T4	9	G-23	109112	PL9S/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	600	12000	6.6"
T4	9	G-23	109144	PL9S/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	600	12000	6.6"
T4	9	G-23	109116	PL9S/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	600	12000	6.6"
T4	9	G-23	109118	PL9S/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	600	12000	6.6"
T4	13	GX23	109126	PL13S/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	825	12000	7.2"
T4	13	GX23	109128	PL13S/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	825	12000	7.2"
T4	13	GX23	109130	PL13S/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	825	12000	7.2"
T4	13	GX23	109132	PL13S/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	825	12000	7.2"
DOUBLE TUBE 2-PIN											
T4	9	G23-2	109110	PL9D/27/ECO	Warm White, EOL	1/50	2700	82	525	12000	4.3"
T4	9	G23-2	109120	PL9D/41/ECO	Cool White, EOL	1/50	4100	82	525	12000	4.3"
T4	13	GX23-2	109146	PL13D/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	900	12000	4.7"
T4	13	GX23-2	109148	PL13D/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	900	12000	4.7"
T4	13	GX23-2	109150	PL13D/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	900	12000	4.7"
T4	13	GX23-2	109149	PL13D/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	900	12000	4.7"
T4	18	G24d-2	109152	PL18D/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	1200	12000	6.0"
T4	18	G24d-2	109154	PL18D/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	1200	12000	6.0"
T4	18	G24d-2	109156	PL18D/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	1200	12000	6.0"
T4	18	G24d-2	109159	PL18D/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	1200	12000	6.0"
T5	22	GX32d-2	109862	PL22D/27	Warm White	1/50	2700	82	1200	12000	6.1"
T5	22	GX32d-2	109864	PL22D/50	Natural White	1/50	5000	82	1200	12000	6.1"
T4	26	G24d-3	109158	PL26D/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	1800	12000	6.8"
T4	26	G24d-3	109160	PL26D/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	1800	12000	6.8"
T4	26	G24d-3	109162	PL26D/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	1800	12000	6.8"
T4	26	G24d-3	109163	PL26D/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	1800	12000	6.8"
T5	28	GX32d-3	109870	PL28D/28	Warm White	10/50	2800	82	1600	12000	6.7"
T5	28	GX32d-3	109868	PL28D/50	Natural White	10/50	5000	82	1600	12000	6.7"
SINGLE TUBE 4-PIN ELECTRONIC											
T4	13	G24q	109134	PL13S/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	825	12000	6.7"
T4	13	G24q	109136	PL13S/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	825	12000	6.7"
T4	13	G24q	109138	PL13S/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	825	12000	6.7"
T4	13	G24q	109140	PL13S/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	825	12000	6.7"
DOUBLE TUBE 4-PIN ELECTRONIC											
T4	13	G24q-1	109037	PL13D/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	900	12000	5.2"
T4	13	G24q-1	109035	PL13D/E/30/ECO	Soft White, EOL, Eco-Shield®	1/50	3000	83	900	12000	5.2"
T4	13	G24q-1	109038	PL13D/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	900	12000	5.2"
T4	13	G24q-1	109039	PL13D/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	900	12000	5.2"
T4	13	G24q-1	109122	PL13D/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	900	12000	5.2"
T4	18	G24q-2	109010	PL18D/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	1200	12000	5.8"
T4	18	G24q-2	109012	PL18D/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	1200	12000	5.8"
T4	18	G24q-2	109013	PL18D/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	1200	12000	5.8"
T4	18	G24q-2	109074	PL18D/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	1200	12000	5.8"
T4	26	G24q-3	109090	PL26D/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	1800	12000	6.5"
T4	26	G24q-3	109092	PL26D/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	1800	12000	6.5"
T4	26	G24q-3	109094	PL26D/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	1800	12000	6.5"
T4	26	G24q-3	109096	PL26D/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	1800	12000	6.5"
TRIPLE TUBE 4-PIN ELECTRONIC											
☼ T4	18	GX24q-2	44800	PL18T/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	1200	12000	4.6"
☼ T4	18	GX24q-2	44801	PL18T/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	1200	12000	4.6"
☼ T4	18	GX24q-2	44803	PL18T/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	1200	12000	4.6"
☼ T4	18	GX24q-2	44804	PL18T/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	1200	12000	4.6"
T4	26	GX24q-3	109020	PL26T/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	1800	12000	5.2"
T4	26	GX24q-3	109022	PL26T/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	1800	12000	5.2"
T4	26	GX24q-3	109024	PL26T/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	1800	12000	5.2"
T4	26	GX24q-3	109076	PL26T/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	1800	12000	5.2"
T4	32	GX24q-3	109026	PL32T/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	2400	12000	5.8"
T4	32	GX24q-3	109028	PL32T/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	2400	12000	5.8"
T4	32	GX24q-3	109030	PL32T/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	2400	12000	5.8"
T4	32	GX24q-3	109070	PL32T/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	2400	12000	5.8"
T4	42	GX24q-4	109032	PL42T/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	3200	12000	6.6"
T4	42	GX24q-4	109034	PL42T/E/35/ECO	White, EOL, Eco-Shield®	1/50	3500	82	3200	12000	6.6"
T4	42	GX24q-4	109036	PL42T/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	3200	12000	6.6"
T4	42	GX24q-4	109072	PL42T/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	3200	12000	6.6"
☼ T4	57	GX24q-5	44806	PL57T/E/27/ECO	Warm White, EOL, Eco-Shield®	1/50	2700	82	4200	12000	7.8"
☼ T4	57	GX24q-5	44807	PL57T/E/41/ECO	Cool White, EOL, Eco-Shield®	1/50	4100	82	4200	12000	7.8"
☼ T4	57	GX24q-5	44808	PL57T/E/50/ECO	Natural White, EOL, Eco-Shield®	1/50	5000	82	4200	12000	7.8"
SPIRAL TUBE 4-PIN ELECTRONIC											
T4	13	GX24q-1	109692	PL13SP/E/27	Warm White	1/50	2700	82	900	12000	3.5"
T4	13	GX24q-1	109694	PL13SP/E/41	Cool White	1/50	4100	82	900	12000	3.5"
T3	26	G24q-3	109696	PL26SP/E/27	Warm White	10/50	2700	82	1600	12000	4.1"
T3	26	G24q-3	109698	PL26SP/E/41	Cool White	10/50	4100	82	1600	12000	4.1"
FLAT QUAD 4-PIN											
T4	27	GX10q-4	109238	FML27/NDL	Warm White	1/50	5000	82	1500	12000	5.9"
R40 4-PIN ELECTRONIC											
R40	26	G24q-3	109382	PL26/R40/E/30	Soft White Flood	6/24	3000	82	1450	8000	6.1"
R40	26	G24q-3	109388	PL26/R40/E/50	Natural White Flood	6/24	5000	82	1450	8000	6.1"

☼ NEW ITEM!

(Hg) Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.
Visit www.lamprecycle.org for disposal information for your state or local government.

Halco Lighting Technologies | P.O. Box 2834 | Norcross, GA 30091-2834

Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822

halcolighting.com

Atlanta | Cleveland | Houston | Phoenix