

## DESCRIPTION

The H7 recessed housings are the standard in the industry for both commercial and residential applications. The wide variety of trims available allows a number of different lighting effects to be created with one basic housing. The H7ICTNB is designed for installations where the housing will be in direct contact with insulation.

## APPLICATION

The H7ICTNB is designed to save installation time. It is designed without a socket plate for use with socket supporting trims only. With these trims there is no need to spend time removing the socket from the socket plate and the socket plate from the housing.

## DESIGN FEATURES

### A...Housing

Aluminum construction for greater heat dissipation.

### B...Plaster Frame

Housing adjusts in plaster frame to accommodate up to 1-3/4" ceiling thickness. Plaster frame features include:

- Regressed locking screw for securing hanger bars
- Cutouts for easily crimping hanger bars in position
- Halo name embossed on plaster frame Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box.

### C...Junction Box

Junction box features include:

- Listed for through branch circuit wiring
- Positioned to accommodate straight conduit runs
- Seven 1/2" trade size conduit knockouts with true pry-out slots
- Slide-N-Side™ connectors allow non-metallic sheathed cable to be installed without tools and without removing

knockouts. Accepts a wider range of non-metallic sheathed cable – the standard cable types used in lighting for both U.S. and Canada.

- Allows wiring connections to be made outside the junction box
- Simply insert the cable directly into the trap after connections are made
- accommodates the following standard non-metallic sheathed cable types: (US) #14/2, #14/3, #12/2, #12/3 (Canada) #14/2, #14/3, #12/2

### D...GOT NAIL! Pass-N-Thru™ Bar Hangers

Bar Hanger Features include:

- Pre-installed nail easily installs in regular lumber, engineered lumber and laminated beams
- Safety and guidance system prevents snagging, ensures smooth straight nail penetration and allows bar hangers to be easily removed if necessary.
- Automatic levelling flange aligns the housing and lets you hold the housing in place with one hand while driving nails
- Housing can be positioned at

Catalog #	Type
Project	
Comments	
Prepared by	Date



## H7ICTNB

**6" Insulated Ceiling Recessed Housing No Socket Bracket**

**6" TRIMS**

**FOR USE IN INSULATED CEILINGS**

**FOR DIRECT CONTACT WITH INSULATION**

**FOR USE WITH SOCKET SUPPORTING TRIMS**

This housing is AIR-TITE when used with the following Trims:

- 170PS
- 171PS
- 173PS
- 78PAT
- 30 (All Styles)
- 430 (All Styles)
- ERT712 Series
- ERT713 Series
- ERT725 Series



**SLIDE-N-SIDE III JUNCTION BOX**


**UPGRADE FEATURES:**

- SLIDE-N-SIDE™ JUNCTION BOX
- PASS-N-THRU™ BAR HANGERS
- REGRESSED LOCKING SCREW
- HALO ID ON PLASTER FRAME


ADV042490

Supersedes ADV031585  
ADV023108 & ADV000302  
9/04

TAB: Recessed Incandescent  
Sheet 21



Slide-N-Side III™ Junction Box



Ordering information on reverse

**COOPER LIGHTING**

TRIMS

ORDERING INFORMATION

SAMPLE NUMBER: H7ICTNB-30PAT

Order housing, trim and accessories separately.

Housing	Trims	Accessories
---------	-------	-------------

H7ICTNB=AIR-TITE Insulated Ceiling Housing, No Socket Bracket

REFLECTORS



30

**AIR-TITE Super Trim**  
**60W A19, 75W PAR30, 75W R30, 65W BR30, 75W PAR30L, 60W PAR38**  
 30CAT=Specular Clear, Air-Tite  
 30RGAT=Residential Gold, Air-Tite  
 30HAT=Haze, Air-Tite  
 30SNAT=Satin nickel  
 OD: 7 1/4" (184mm)



30

**AIR-TITE Super Trim**  
**40W A19, 50W PAR30, 75W R30, 65W BR30, 75W PAR30L, 50W PAR38**  
 30SBAT=Specular Black, Air-Tite  
 OD: 7 1/4" (184mm)



404

**Specular Reflector**  
**60W A19**  
 404C=Specular Clear  
 404H=Haze Reflector  
 404RG=Residential Gold  
 404SN=Satin Nickel  
 OD: 7 1/4" (184mm)



4041

**Self Flanged Reflector**  
**60W A19**  
 4041P=White  
 OD: 7 1/4" (184mm)

BAFFLES



30

**AIR-TITE Super Trim**  
**40W A19, 75W R30, 65W BR30, 60W PAR38, 75W PAR30, 75W PAR30L**  
 30PAT=Black Baffle  
 30WAT=White Baffle  
 OD: 7 1/4" (184mm)

ADJUSTABLES



74

**Eyeball**  
**75W PAR30**  
 74P=White Eyeball  
 OD: 8" (203mm)



77

**Eyeball**  
**50W R20**  
 77P=White Eyeball  
 OD: 8" (203mm)



78

**Eyeball**  
**75W R30**  
 78P=White Eyeball  
 78SL=Silver Eyeball  
 78B=Brass Eyeball  
 78PB=Polished Brass Eyeball  
 78SN=Satin Nickel  
 78PAT=White Eyeball (converts H7ICT and H7RICT to AIR-TITE Construction)  
 OD: 8" (203mm)



420

**Coilex Regressed Eyeball**  
**50W PAR30L, 60W BR30**  
 420P=Black Baffle, White Eyeball  
 420PB=Black Baffle, Polished Brass Eyeball  
 420W=White Baffle, White Eyeball  
 OD: 7 1/4" (184mm)

DIFFUSERS



170

**Glass Albalite Lens**  
**40W A19**  
 170P=White Trim Ring  
 170PS=White Trim Ring, Shower Light  
 OD: 8" (203mm)



171

**Plastic Drop Opal**  
**40W A19**  
 171P=White Trim Ring  
 171PS=White Trim Ring, Shower Light  
 OD: 8" (203mm)



172

**Shower Light**  
**60W A19, 50W PAR30**  
 172PS=White Trim Ring, Shower Light  
 172SNS=Satin Nickel Trim Ring, Shower Light  
 OD: 7 3/4" (197mm)



173

**Glass Fresnel Lens**  
**40W A19**

173P=White Trim Ring  
 173PS=White Trim Ring, Shower Light  
 OD: 8" (203mm)

OPEN TRIMS



300

**Open**  
**75W R30, 75W PAR30, 75W PAR30L, 65W BR30**  
 300P=White  
 300SN=Satin Nickel  
 OD: 7 1/4" (184mm)



327

**Splay Trim with Integral socket Support**  
**65W BR30, 75W PAR30, 75W PAR30L**  
 327P=White Splay  
 OD: 7 1/4" (184mm)

WALL WASH



430

**Baffle Wall Wash**  
**40W A19**

430P=Black Baffle, White Scoop, White Trim Ring  
 430W=White Baffle, White Scoop, White Trim Ring  
 OD: 7 1/4" (184mm)

Accessories

Metal Trim Rings

Compatible with 404  
**TRM6P**=White Metal  
**TRM6PB**=Polished Brass  
**TRM6C**=Chrome  
**TRM6MB**=Black Metal  
**TRM6SL**=Silver  
**TRP7MB**=Black Plastic  
**TRM6SN**=Satin Nickel

Oversize Trim Rings

For use when ceiling opening is cut too large. Compatible with 404.  
**OT400P**=9 1/4" White Metal  
**OT403P**=8" White Plastic

Note: Specifications and Dimensions subject to change without notice.

Visit our web site at [www.cooperlighting.com](http://www.cooperlighting.com)