LED-8027M Post Top / Site / Wall Pack

 SKU (USA)
 SKU (Canada)
 Description

 LED-8027M30
 LED-8027M30C
 100W 3000K

 LED-8027M42
 LED-8027M42C
 100W 4200K


 LED-8027M57
 LED-8027M57C
 100W 5700K



Technical Specifications			
Models US/CAN	LED-8027M30/ LED-8027M30C	LED-8027M42/ LED-8027M42C	LED-8027M57/ LED-8027M57C
ССТ	3000K	4200K	5700K
Power Consumption	100 watts		
Replaces	250w MH/HPS		
Mounting	E39		
Voltage	120-277VAC (USA) 120-347VAC (CANADA)		
LED Type	300 Samsung #5630 SMD		
Beam Angle	360		
Dimmable	No		
Operating Temp	-40°F - +122°F		
Rated R70 Life	Up to 50,000 Hrs.		
Warranty	5 Year Limited*		
LM79 Specifications	Yes	Yes	Yes
Power (W)	100.1	96.3	95.7
ССТ	3273	4324	5716
Light Output	10603	10669	10083
Efficacy	105.92	110.8	105.36
THD @ 277V	n/a	18.85%	18.03%
PF @ 277V	0.941	0.94	0.936
CRI:	84.6	84.6	86.8
R9	16	17	37
Duv	-0.0022	-0.0006	-0.0035
Packaging	4 / Master Carton		
Unit	7.3" x 7.3" x 13.78" 3.3 lbs.		
Master	15.4" x 15.4" x 14.4" 14.6 lbs.		



NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.











Description:

100W LED retrofit lamp to replace MH and HPS lamps up to 250w, E39 Mogul base. Integrated insect/dust screen. UL damp rated approved for <u>fully enclosed</u> fixtures.

Features:

- Replaces 250w HID Lamps
- 120-277V or 120-347V (Canada)
- UL Classified for damp environments (USA & Canada)
- UL approved for fully enclosed fixtures (USA & Can)
- Active Cooling Fan >70,000 hr. rated life
- 50,000 rated life
- 5 year limited warranty (see website for details)

Applications:







Wall Pack

Shoe Box

Post Top

Installation Notes:

- When installing LED-8000 series retrofit lamps within HID fixtures, ballast must be bypassed when present.
- 8000 series retrofits are UL damp rated, sealing the fixtures after installation will deliver best results.
- Installing surge/lightning protectors is highly recommended and helps to eliminate premature driver failure caused by surges and other power fluctuations.



188 S. Northwest Highway • Cary, IL 60013 (847) 380-3540 • FAX: (847) 380-3542 www.led-llc.com