

# LED Low Bay/Site Utility Series



<b>Stock No.</b>	<b>Product Description</b>
<b>LED-8025-DL</b>	<b>GL-120/277-52-54-DL (Daylight) Utility Light</b>
<b>LED-8025-NW</b>	<b>GL-120/277-52-54-NW (Neutral White) Utility Light</b>

## Description:

Fully encapsulated, 120/277 Volt, E26 medium base mounting that integrates energy saving LED technology into a powerful yet energy saving SMD low bay/utility lamp. Available in Daylight (DL) or Neutral White (NW).

- 52 Watts
- 120 - 277 Volt operation
- Daylight DL (5700K), Neutral White NW (3000K)
- Lumens: 3200(DL), 3100(NW)
- 54 on-board SMD LEDs
- Up to 50,000 hour lamp life
- Operating range: -30C to 50C
- Not Dimmable
- 5 year warranty (see www.led-llc.com for full details)
- Patented under 29/415,685
- UL Listed Damp Location
- LM79, IES available
- Active Cooling Delta 70K Hr Fan

## Applications:



LED Low Bay/Site Utility Series lamps can impact energy usage and costs in a major way for communities and housing developments with minimal to no maintenance costs thanks to the up to 50,000 hour lamp life.

- Site / Roadway / Post Top
- Security lighting
- Parks and quads
- Municipal lighting
- Parking Garage
- Low Bay Applications

**NOTE: When retrofitting LED to HID fixture, ballast must be bypassed when present. Eliminating the ballast saves additional costs related to maintenance, energy consumption and performance. Additionally, by-passing ballast will insure no RFI interference.**

## Packaging:

Master-pack: 4 each



## Technical Specifications:

Note: All specification information falls within a  $\pm$  2% range and is subject to change

<b>Bulb Type:</b>	<b>Site/Warehouse</b>	<b>Mounting:</b>	<b>E26 Medium Base</b>
<b>Bulb Material:</b>	<b>Alum/Polycarbon</b>	<b>Replaces:</b>	<b>175W MH</b>
<b>UV:</b>	<b>None</b>	<b>Life Time:</b>	<b>Up to 50,000 Hrs.</b>
<b>Output Power:</b>	<b>52W</b>	<b>Input Voltage:</b>	<b>AC 120 – 277V</b>
<b>Lumens:</b>	<b>3200(DL) 3100(NW)</b>	<b>Beam Angle:</b>	<b>360 °</b>
<b>Dimensions:</b>	<b>7-7/8" x 5-7/8"</b> <b>200mm x 149mm</b>	<b>Kelvin Temp:</b>	<b>(DL) 5700K</b> <b>(NW) 3000K</b>
<b>Lumen per Watt:</b>	<b>60</b>	<b>LEDs:</b>	<b>54 SMD LEDs</b>
<b>Power Factor:</b>	<b>98</b>	<b>Mercury:</b>	<b>No</b>
<b>CRI:</b>	<b>81</b>	<b>Freq:</b>	<b>50-60Hz</b>

without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.

106 S. Wynstone Park Drive • N. Barrington, IL 60010  
(847) 380-3540 • FAX: (847) 380-3542  
www.led-llc.com



**Light Efficient Design**  
a division of TADD, LLC