
Occupancy/Vacancy Sensing in Classrooms – Switching Solutions

A best-practice classroom combines energy efficiency with a high-quality learning environment. Classroom lighting plays a particularly critical role because of the direct relationship between good lighting and student performance.¹

Classroom Occupancy/Vacancy Sensing with Switching Control

A simple switching solution ensures that lighting is not left on when the classroom is unoccupied, and enables multizone switching for lights near blackboards or smart boards, and the rest of the room.



Bill of materials



Maestro Wireless® switch

MRF2-8S-DV-WH (dual voltage, no neutral)



Maestro Wireless® 2-gang switch CW-2-WH (dual-gang faceplate)



Radio Powr Savr™ occupancy/vacancy sensor (corner-mount) LRF2-OKLB-P-WH

Save 20 - 60% lighting energy² with Lutron occupancy/vacancy sensors






Classroom Occupancy/Vacancy Sensing with Dimming and Daylight Control

Wireless daylight sensors combined with Lutron dimming ballasts automatically adjust electric lights in response to available daylight. Minimize glare and heat gain that disrupt the learning environment, and reduce demand on HVAC systems.

Bill of materials



EcoSystem® H-Series digital ballast EHDT-(base model number)

sensor (corner-mount) LRF2-OKLB-P-WH

Pico® wireless controls

CW-1-WH (single-gang faceplate)

CW-2-WH (dual-gang faceplate)

PICO-FP-ADAPT (Pico faceplate adapter)

PJ-3BRL-GWH-TOI

Radio Powr Savrm occupancy/vacancy



PowPak™ dimming module with EcoSystem RMJ-ECO32-DV-B



Radio Powr Savr daylight sensor LRF2-DCRB-WH

Helps meet ASHRAE Code 90.1-2010

Save up to 70% lighting energy^{2,3} and reduce demand on air conditioning with a dimming and daylighting solution.



Ø





- 1 Phillips, R. W. 1997. Educational Facility Age and the Academic Achievement of Upper Elementary School Students. Unpublished Doctoral Dissertation. University of Georgia.
- 2 VonNieda B, Maniccia D, & Tweed A. 2000. An analysis of the energy and cost savings potential of occupancy sensors for commercial lighting systems. Proceedings of the Illuminating Engineering Society. Paper #43.
- 3 Newsham GR & Birt B. 2010. Demand-responsive lighting: a field study. National Research Council Canada.

www.lutron.com World Headquarters 1.610.282.3800 Technical Support Center 1.800.523.9466 (Available 24/7) Customer Service/Quotes 1.888.LUTRON1 (1.888.588.7661)

@ 05/2012 Lutron Electronics Co., Inc. P/N 368-2650 REV A



