

MaxLite™

ENERGY EFFICIENT LIGHTING PRODUCTS

PRODUCT FOCUS

GU24 SQUATMAX

Compact Fluorescent Lamp



FOR >> Fixtures with
the latest ballast
& socket technology



MLS13GUSWW*



MLS18GUSWW6*



MLS26GUSWW*

- Now with 90°C Max. Ballast Case Temperature
- Extra short MOL to fit Fixtures
- Fits all fixtures with GU24 base
- Long life - up to 10,000 hours
- Saves up to 75% in energy costs
- Instant on, flicker-free

INSTANT START
ISIB
INSTANT BRIGHT



*Energy Star Qualified

MaxLite™ : 1-800-555-5629 Fax: 973-244-7333 info@maxlite.com www.maxlite.com

MaxLite West™ : 1-800-793-1212 Fax: 909-944-1442 info@maxlite.com www.maxlite.com

*All specifications are subject to change without notice

PRODUCT FOCUS **GU24 SQUATMAX**
Compact Fluorescent Lamp



MLS13GUSWW*
10,000 Hour
(7) 6762711312 (3)*

MLS18GUSWW6*
10,000 Hour
(7) 6762711313 (0)*

MLS26GUSWW*
10,000 Hour
(7) 6762711314 (7)*

GU24 SQUATMAX SPECIFICATIONS

| Watts | Order Code | Description | Incandescent Equivalent | Lumens | Lamp Life (Hrs) | Pack Type | Case Pack | Dimensions (W" x MOL") | K |
|-------|------------|---------------------------|-------------------------|--------|-----------------|-----------|-----------|------------------------|------|
| *13 | 11312 | MLS13GUSWW GU24 SquatMax | 60 | 900 | 10,000 | Box | 48 | 3.11 x 2.52 | 2700 |
| *18 | 70442 | MLS18GUSWW6 GU24 SquatMax | 75 | 1150 | 10,000 | Box | 6 | 3.11 x 3.42 | 2700 |
| *26 | 11314 | MLS26GUSWW GU24 SquatMax | 100 | 1600 | 10,000 | Box | 48 | 3.14 x 3.5 | 2700 |

SPECIAL NOTES

- > **GU24:** - 2 year warranty
- For GU24 replacement bulbs visit your local lighting and hardware store or go to www.maxlite.com/GU24.
- Now with 90°C Max. Ballast Case Temperature

APPLICATIONS

- Ceiling fixtures, pendants
- Outdoor fixtures, recess fixtures
- Wall sconces, vanity bars
- Floor & table lamps

BENEFITS

- Now with 90°C Max. Ballast Case Temperature
- Extra short MOL to fit Fixtures
- Fits all fixtures with GU24 base
- Long life - up to 10,000 hours
- Saves up to 75% in energy costs
- Rapid start electronic ballast with flicker-free operation

SPECIFICATIONS

- Ballast Type >> Electronic
- Starting Method >> Instant Start
- Input Line Voltage >> 120VAC
- Input Line Frequency >> 50/60HZ
- Mini. Starting Temp. >> 0°F
- Max. Ballast Case Temp. >> 90°C
- Color Rendering Index >> 84

MAX10493-10

All specifications are subject to change without notice



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.



FCC Certified
*UPC Codes
*Energy Star Qualified

MaxLite™ : 1-800-555-5629 Fax: 973-244-7333 info@maxlite.com www.maxlite.com

MaxLite West™ : 1-800-793-1212 Fax: 909-944-1442 info@maxlite.com www.maxlite.com