


Type

Project

Catalog No.

Lamp/Wattage

ITEM NUMBERS**NTH-138 Dimensions:**

Diameter: 2-1/8"

Length: 3"

Max. Ext.: 5-1/4"

Note: All dimensions are given without lamp installed and vary depending on lamp.

NTH-138B: Black Truly Universal™ Lamp Holder, H-Style**NTH-138B/J:** Black Truly Universal™ Lamp Holder, J-Style**NTH-138B/L:** Black Truly Universal™ Lamp Holder, L-Style**NTH-138W:** White Truly Universal™ Lamp Holder, H-Style**NTH-138W/J:** White Truly Universal™ Lamp Holder, J-Style**NTH-138W/L:** White Truly Universal™ Lamp Holder, L-Style**NTH-138****Truly Universal™ Lamp Holder**

Lamp: 60W PAR16 / 50W R20/PAR20

75W BR30/PAR30 / 250W BR40/PAR38

PRODUCT DESCRIPTION

Lamp holder accepting all sizes of light sources from PAR16 to PAR38 and R20 to BR40. A unique flanged, retractable shroud extends to cover the neck of any light source for a clean appearance that is uncommon to most lamp holders.

FEATURES

- Retractable extension hides lamp neck and screw shell
- Ultra-clean appearance
- Heat resistant Teflon coated wire lead
- Low profile mounting/adjustment arm
- High-strength stainless steel electrical contacts
- One or two circuit track capable

CONSTRUCTION**Socket Enclosure**

0.03" Drawn steel cup contains socket, and two tempered stainless steel springs that secure an extension cover for shielding the base and neck of any lamp source. Extension can also be removed if desired.

Adjustment Arm

0.080" Rigid steel "L-Bracket" connects fixture housing to electrical contact head. Single tightening knob locks vertical angle of fixture.

Socket

Porcelain socket with internal stainless screw shell.

Wiring

Teflon coated wire lead connects socket and housing to electrical contact head. Teflon coating is durable and resists heat degradation from lamp and housing radiation.

Lamp

60W PAR16 Maximum (not included)

50W R20/PAR20 Maximum (not included)

75W BR30/PAR30 Maximum (not included)

250W BR40/PAR38 Maximum (not included)

Contact Head Assembly

"H" Style (standard): Three 0.030 stainless steel contacts mounted in premium plastic housing.

"J" Style: Two contacts and ground contact mounted in premium plastic housing with on/off switch.

"L" Style: Two contacts and ground contact mounted in premium plastic housing.

Finish

Black or white heat rated baked enamel paint. Custom painting or anodizing for special applications are also available. Custom finishes will require lead times that vary depending on vendor schedule. Please consult factor for quotation, and provide either a Dunn Edwards number or color chip for exact matching.

One/Two Circuit Conversion

Positive contact (opposite neutral and ground contacts) is preset to "down" position at the factory, but may be raised to the high position to install onto the second circuit of Nora Lighting's NT-2300 series two-circuit track.

Compatibility

H-Style is compatible with Halo or any other brands configured to Halo 3 (single circuit) or Halo 4 (2 circuit) track system design.

J-Style is compatible with "J" Style track.

L-Style is compatible with "L" Style track.

Note: fixtures may not be compatible with non-Nora monopoint adapters.

Listing

UL Listed as track lighting fitting

**LISTED**