## NTL-150

# Line Voltage Step Cylinder Track Pack Line Voltage Track Pack

Lamps: (3) 75W R/Par30

# **ENORALIGHTING.**

Туре

**Project** 

Catalog No.

Lamp/Wattage

#### PRODUCT DESCRIPTION

One 4' single circuit extruded aluminum track with 20-Amp rated flat, solid integral conductors equipped with two end caps. 3 line voltage stepped "continental" styled track heads with black baffles. The track pack also includes a floating canopy feed, which allows the track to connect to an existing outlet box anywhere along the track.

### **Features**

- · Deep drawn steel housing for high strength and rigidity.
- Completely concealed wiring.
- Fully adjustable, firm angle position.
- · High-strength stainless steel electrical contacts.
- One or two circuit track capable.

#### CONSTRUCTION

#### Track Extrusion

.030 die cast aluminum construction with 0.045 PVC insulators holding 12-gauge flat conductor wiring. Polarity groove is located on face of track to indicate location of grounding conductor.

#### Track Head Housing

0.030 Deep drawn steel construction with simple, yet decorative design. All edges are softened for aesthetic appearance.

#### Raffle

0.085 Black finished phenolic high rated plastic baffle. Provides finished appearance and assists in eliminating glare from housing interior.

#### Structural Arm

Extruded 0.055 aluminum arm connects fixture housing to electrical contact head. Internal tightening mechanism maintains desired lamp aiming angles. Structural arm also functions as wire way, completely concealing lead wire from socket to contact head.

#### Socket

Porcelain jacketed aluminum screw thread medium base socket.

## **Contact Head Assembly**

Three 0.030 stainless steel contacts mounted in high heat rated plastic housing.

### One/Two Circuit Conversion

Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

### Electrical

2400 Watts, 120V input, 60Hz.

### Dimming

Nora track may be dimmed with any approved incandescent dimmer.


### Lam

- 75W R/Par30 lamp (not included).

### Finishes

White heat rated baked enamel paint.

#### **DIMENSIONS**



 TRACK:
 TRACK HEAD:

 Height:
 11/16"
 Diameter:
 4-3/8"

 Length:
 4'
 Length:
 6"

 Width:
 1-7/16"
 Max. Extension:
 9"

## Compatibility

Nora track fixtures are interchangeable with Halo, Catalina, Hampton Bay, Halo-Edison, or any other brands configured to Halo 3 conductor track design.

Note: Fixtures may not be compatible with non-Nora transformers or monopoint adapters.

### **Optional Accessories**

NT-339 Barn Door for R/Par30

NT-342 Black Louver for R/Par30 (Must use NT-339 or NT-345)

NT-345 Black Holder for R/Par30

## **Labels and Listings**

UL Listed as track lighting fitting. UL Listed for indoor, dry location.



## Create a complete catalog number: Example: NTL-150 / NT-345

Track Pack - select one hox from each column

Catalog No.	Lamp	Wattage	Finish	
NTL-150	R/Par30	75	W	

Optional Accessories				
Catalog No.				
NT-339				
NT-342				
NT-345				

Finishes: W = Whit

# **NTL-150 Accessories**

NTE-130 Accessories				
NT-339	Barn Door for R/Par30			
NT-342	Black Louver for R/Par30 (Requires NT-339 or NT-345)			
NT-345	Black Holder for R/Par30			