

Features/Benefits

- High Lamp Efficacy up to 67 LPW.
- Excellent Color Rendering 82 Color Rendering Index (CRI).
- Available in 5, 7, 9 and 13 wattages.
- Long Life 10,000 hour ave. rated life.
- Designed for use with magnetic ballasts integral starter cuts installation wiring costs and permits use of small choke ballasts.

Applications

· Ideal for Task Lighting, Corridor, Security, General Lighting.

Notes

- For expected lamp lumen output, commercial ballast manufacturers can advise the appropriate ballast factor for each of their ballasts when they are informed of the designated lamp. The ballast factor is a multiplier applied to the designated lamp lumen output. (204)
- Rated average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently. (202)
- Approximate Initial Lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is
 measured during operation on a reference ballast under standard laboratory conditions. (203)
- Design Lumens are the approximate lamp lumen output at 40% of the lamp's Rated Average Life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions. (208)


| Product data | | |
|--------------------------|-------------------------------|--|
| Product Number | 146837 | |
| Full product name | PL-S ALTO 13W/830 GX23/2P 1CT | |
| Ordering Code | 146837 | |
| Pack type | 1 Lamp in a Folding Carton | |
| Pieces per Sku | 1 | |
| Skus/Case | 50 | |
| Pack UPC | 046677146832 | |
| EAN2US | | |
| Case Bar Code | 50046677146837 | |
| Successor Product number | | |




| Product data | | |
|-----------------------|---|--|
| Base | GX23 [Two-Pin Compact Fluorescent; high prehea] | |
| Base Information | 2P | |
| Execution | /2P [2 Pins] | |
| Packing Type | 1CT [1 Lamp in a Folding Carton] | |
| Packing Configuration | 5X10CC | |
| Avg. Life | 10000 hr | |
| Ordering Code | PL-S 13W/830/2P/ALTO | |
| Pack UPC | 046677146832 | |
| Case Bar Code | 50046677146837 | |
| Watts | 13W | |
| Lamp Voltage | 56 V | |
| Dimmable | No | |
| Color Code | 830 [CCT of 3000K] | |
| Color Rendering Index | 82 Ra8 | |
| Color Designation | Warm White | |
| Color Description | 830 Warm White | |
| Color Temperature | 3000 K | |
| Initial Lumens | 810 Lm | |
| Overall Length C | 177.7 mm | |
| Diameter D | 28 mm | |
| Diameter D1 | 13 mm | |
| Product Number | 146837 | |
| | | |




PL-S 13W






Base GX23







PL-S/830 PL-S/830

