



# 50W Med 120V PAR30L SP 16D CL 1 CT

## Product family description

Philips Halogen PAR lamps will provide bright, white light across the product line and feature excellent beam qualities for accent or ambient lighting. Their optimized coil and burner design allows for clear, crisp lighting effects with excellent color rendering, making it easy to optimize the look and feel of your store and your merchandise.

## Features

- Beam spreads ranging from Spot and Flood to Wide flood, with wattages from 50-75W.
- Philips Halogen lamps last 2000–3500 hours rated average life†.
- Bright, White Light.
- Optimized coil and burner design allows for clear, crisp lighting effects with excellent color rendering.
- Available in 50, 60 and 75 Watts Spot, Flood, and Wide Flood.
- †Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not.

## Benefits

- Reduced maintenance and operating costs.
- Create a variety of atmospheres and provide a comfortable shopping experience.
- Variety of beam spreads and wattages.

## Application

- Ideal for retail, residential, and commercial applications. For indoor and outdoor use.

## Notes

- To avoid deterioration of lampholder by heat, use only heat resistant lampholders or fixtures listed by a nationally recognized electrical testing organization for use with reflector or PAR lamps. (82)

# PHILIPS

- PAR Halogen Caution Notice: Before using bulb, see operating instructions on inside flap. Adherence to the operating instructions will reduce the risk of personal injury or fire. The filament capsule contained inside this glass bulb is pressurized, operates at high temperatures and could unexpectedly shatter. Should the outer bulb break, particles of extremely hot glass could be discharged into the fixture and/or the surrounding environment, thereby creating a risk of personal injury or fire. Operating Instructions: Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.
- Rated average life is the length of operation (in hours) at which point an average of 50% of the lamps will still be operational and 50% will not. (93)
  - —For indoor or outdoor use. A weather-protected fixture is recommended for wet locations.
  - —Suitable for use in open fixtures.
  - —Do not exceed the maximum wattage rating of the fixture.
  - —Do not use if outer glass is scratched or broken since it may break during operation or removal.
  - —If outer glass breaks the lamp may continue to light, however, immediately discontinue use.
  - —Due to the heat that radiates from the bulb, do not use in close proximity to combustible materials or objects susceptible to drying or fading.
  - —Manage in accord with disposal laws. (86)

Product data	
Product Number	229237
Full product name	50W Med 120V PAR30L SP 16D CL ICT
Ordering Code	50PAR30L/HAL/SP16
Pack type	1 Lamp in a Folding Carton
Pieces per Sku	1
Skus/Case	15
Pack UPC	046677229238
EAN2US	
Case Bar Code	50046677229233
Successor Product number	
Base	Medium [Single Contact Medium Screw]
Base Information	Brass [Brass Base]
Bulb	PAR30L [PAR 3.75 inch/95mm Long]
Bulb Material	Hard Glass
Bulb Finish	Clear
Reflector Finish	Aluminized
Filament Shape	CC-8 [Axial]
Operating Position	Universal [Any or Universal (U)]
Packing Type	ICT [1 Lamp in a Folding Carton]
Packing Configuration	15



Product data	
Atmosphere	Gas
RatedAvgLife(See Family Notes)	
Ordering Code	50PAR30L/HAL/SP16
Pack UPC	046677229238
Case Bar Code	50046677229233
Watts	50W
Voltage	120V
Beam Description	Spot
Beam Angle	16D
Approx. MBCP	3800 cd
Color Rendering Index	100 Ra8
Color Temperature	2900 K
Initial Lumens	590 Lm
Max Overall Length (MOL) - C	4.5 in
Diameter D	3.75 in
Product Number	229237



©2009 Koninklijke Philips Electronics N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Document order number : 0000 000 00000