



# Low Pressure Sodium - SOX

SOX 55W 1SL

High energy efficiency low pressure sodium lamps for indoor and outdoor applications.

## Product data

### • Product Data

Product number	321513
Full product name	SOX 55W BY22d 1SL
Short product name	SOX 55W BY22d 1SL
Pieces per Sku	1
eop_pck_cfg	12
Skus/Case	12
Bar code on pack	8711500600134
Bar code on case	8711500600141
Logistics code(s)	928146000028
tpd_ilcos_cd	LS-55-BY22d
eop_net_weight_pp	300.000 gr

### • General Characteristics

Base	DC Bayonet
Bulb	T15 [Diameter: 1.97 inch]
Operating Position	Base Up +/- 110 D [Hanging +/-110D or Base Up (BU)]
Life to 5% failures	6000 hr
Life to 20% failures	12000 hr
RatedAvgLife(See Family Notes)	18000 hr

### • Electrical Characteristics

Watts	55 W
Lamp Wattage	56.0 W
Lamp Voltage	109 V
Lamp Current	0.59 A

Dimmable No

### • Environmental Characteristics

Mercury (Hg) Content 0 mg

### • Light Technical Characteristics

Color Temperature	1800 K
Initial Lumens	7800 Lm
Luminous Efficacy	140 Lm/W
Lamp EM	
Lumen Maintenance 2000h	102 %
Lumen Maintenance 5000h	100 %
Luminance Average EM	9 cd/cm <sup>2</sup>


### • Product Dimensions

Overall Length C	425 mm
Diameter D	52 mm

### • Luminaire Design Requirements

Cap-Base Temperature	150 C
Bulb Temperature	150 C

## Dimensional drawing



Product	C (Max)	D (Max)
SOX 55W BY22d T50	425	52



© 2010 Koninklijke Philips Electronics N.V.  
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

[www.philips.com/lighting](http://www.philips.com/lighting)

2010, November 23  
data subject to change