



EnduraLED PAR20 Indoor Flood

7PAR20/END/F25 2700-280 DIM 6/1

Philips EnduraLED PAR20 Dimmable Indoor Flood LED lamps bring innovation to familiar application and delivery excellent dimming performance.

Product data

• General Characteristics

Cap-Base	E26
Bulb	PAR20 [PAR20 mm]
Rated Avg. Life (Hours)	45000 hr

Voltage	120 V
Line Frequency	60 Hz
Power Factor	0.72 -
Lamp Current mA	85 mA
Dimmable	Yes

• Light Technical Characteristics

Color Code	WW
Color Designation	Warm White
Beam Angle	25 D
Beam Description	- [-]
Correlated Color Temperature	2700 K
Approximate Lumens	310 Lm
Approx. MBCP	1300 cd
CRI	80
Color Temp. (Kelvin)	2700 K [CCT 2700K]

• Product Dimensions

Overall Length C [in]	3.48 (max) in
-----------------------	---------------


• Product Data

Product number	418574
Full product name	7PAR20/END/F25 2700-280 DIM 6/1
Short product name	7PAR20/END/F25 2700-280 DIM 6/1
Pieces per Sku	1
eop_pck_cfg	6
Skus/Case	6
Bar code on pack	46677418571
Bar code on case	50046677418576
Logistics code(s)	929000202104
eop_net_weight_pp	0.156 kg

• Electrical Characteristics

Wattage	7 W
Wattage Technical	7.0 W

Dimensional drawing



7W, PAR20, Dimmable

Product	C (Norm)	D (Norm)
LED 7W 2700K 120V PAR20 25D DIM	-	-



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, October 7
data subject to change