

PAR20 Dimmable LED Lamps with AirFlux Technology

8PAR20/END/F25 4000 DIM 6/1

Philips PAR20 Dimmable LED Lamps with AirFlux Technology provide optimal thermal efficiency in a sleek, lightweight design.

Product data

General Characteristics

Cap-Base Bulb Rated Avg. Life (Hours) E26 PAR20 [PAR20 mm] 45000 hr

• Light Technical Characteristics

Color Code Color Designation Beam Angle Beam Description Correlated Color Temperature	CW Cool White 25 D 25D [Medium beam] 4000 K
Approximate Lumens CRI Luminous Efficacy Lamp Color Temp. (Kelvin) Rated Luminous Flux	470 Lm 85 58.75 Lm/W 4000 K [CCT 4000K] 470 Lm

• Electrical Characteristics

Wattage	8 W
Wattage Technical	8 W
Voltage	120 V
Line Frequency	60 Hz
Power Factor	0.9 -
Lamp Current mA	78 mA

Warnings and Safety

• Suitable for use in damp locations.



Wattage Equivalent Starting Time	50 W 0.5 s
Measuring Conditions	200001/
Switching cycleProduct Dimensions	20000X
 Product Dimensions 	
Overall Length C Overall Length C	81 mm 3.189 (max) in
[inch] Diameter D	63 mm

Yes

• Product Data

Dimmable

Product number Full product name Short product name


Pieces per Sku eop_pck_cfg Skus/Case Bar code on pack Bar code on case Logistics code(s) eop_net_weight_pp 426148 8PAR20/END/F25 4000 DIM 6/1 120V END PAR20 8W 25D 4000K DIM SM 1 6 6 46677426149 50046677426144 929000233201 0.117 kg

- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.



PAR20 Dimmable LED Lamps with AirFlux Technology

Dimensional drawing



8PAR20/END/F25 4000 DIM 6/1

Product	C (Norm)	C1 (Max)	D (Norm)	D1 (Norm)
LED 8W E26 4000K 120V PAR20 25D	81	3.189	63	2.48



E26



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting