

# INCANDESCENT LAMPS

Watts	Bulb	Base	Product Number	Symbols, Footnotes	Ordering Code	Volts	Pkg. Qty.‡	Description	Class Filament	LCL (In.)	MOL (In.)	Rated Avg. Life (Hrs.) <sup>(93)</sup>	Approx. MBCP <sup>†</sup>	Lumens		
<b>INCANDESCENT LAMPS (BY WATTAGE) CONTINUED</b>																
85	BR30	Med.+++	16766-8	▲ X (87)	85BR30/FL55/LL 6/1	120	6	Long Life Reflector Flood	C,CC-6			5%	2500	700	855	
			16767-6	▲ X (87)	85BR30/SP20/LL 6/1	120	6	Long Life Reflector Spot	C,CC-6			5%	2500	3100	865	
	BR40	Med.+++	22527-6	▲ X ✓ (87)	85BR/FL60	120	24	Reflector Flood	C,CC-6			6½	2000		925	
			22528-4	▲ X ✓ (87)	85BR/FL60	130	24	Reflector Flood	C,CC-6			6½	2000		925	
90	A19	Med.	22243-0	▲ ✓ \$	100A-90A/EW	120	48	Frost Econ-o-watt	C,CC-6			4%	750		1445	
			22244-8	▲ ✓ \$	100A-90A/EW	130	48	Frost Econ-o-watt	C,CC-6			4%	750		1525	
			15001-1	▲ \$	100A-90A/99EW	120-130	48	Frost Econ-o-watt Extended Service Ratings @ 120V =84W	C,CC-6			4%	1500		1400	
												2550		1220		
95	A19	Med.*	21459-3	▲	95A	120	48	Frost	C,CC-6			4%	750		1600	
			21474-2	▲	95A	130	48	Frost	C,CC-6			4%	750		1600	
			21473-4	▲	95A/CL	130	48	Frost	C,CC-6			4%	750		1600	
			21504-6	▲	95A/W/TP 12/4	120	48	Soft White	C,CC-6			4%	750		1550	
			21460-1	▲	95A/W 24/4	120	96	Soft White	C,CC-6			4%	750		1550	
			21818-0	▲	95A/WL 12/4	120	48	Soft White Long Life	C,CC-6			4%	1125		1500	
			21461-9	▲	95A/WL 24/4	120	96	Soft White Long Life	C,CC-6			4%	1125		1500	
100	A19	Med.++	37474-4	▲ ✓	100A	120	48	Frost	C,CC-6			4%	750		1600	
			13684-6	▲ ✓	100A	120	48	Frost	C,CC-8			4%	750		1710	
			37476-9	▲ ✓	100A	130	48	Frost	C,CC-6			4%	750		1590	
														2120		1205
			15934-3	▲ ✓	100A/TG	130	48	Frost	C,CC-6			4%	750		1590	
			13999-7	✓	100A 120/I PRO	130	120	Frost ProPack Lamp	C,CC-6			4%	750		1590	
			22979-9	▲ ✓	100A/99	130	48	Frost Extended Service Ratings @ 120V =88W	C,CC-6			4%	2500		1470	
														7075		1110
			37527-9	▲	100A/CL	130	48	Clear	C,CC-6	3½		4%	750		1590	
														2120		1205
			13998-9		100A/CL 120/I PRO	130	120	Clear ProPack Lamp	C,CC-6	3½		4%	750		1615	
			13254-8	▲ ✓	100A/W 12/4	120	48	Soft White	C,CC-6			4%	750		1620	
			13561-6	▲	100A/NTL 12/4	120	48	Natural Light Standard	C,CC-6			4%	750		1350	
			15130-8		100A/NTL/2XL 12/4	120	48	Natural Light Standard	C,CC-6			4%	1500		1,210	
			15008-6	▲	100A/CL/LL 12/2	120	24	Clear Long Life	C,CC-6			4%	1500		1440	
			16740-3	▲	100A/WL 24/4	120	96	Soft White Long Life	C,CC-8			4%	1500		1440	
13255-5	▲	100A/W/TP 24/4	120	96	Soft White Tra-Pak	C,CC-6			4%	750		1620				
22581-3	▲ ✓ □	100A/YL 12/2	120	24	Bug-A-Way® Yellow Longer Life	C,CC-6			4%	1350						
16862-5	▲	100A/WL 12/4	120	48	Soft White Long Life	C,CC-6			4%	1500		1440				
	A19	Med.LHT	37414-0	(18)	100A/LHT	120-130	48	Frost	C,CC-6			4%	750		1560	

For the most current product information, go to the e-catalog on [www.philips.com](http://www.philips.com)  
 Incandescent symbols and footnotes located on page 51

