400

135

ELECTRICAL

Lamp Oper. Voltage (Nom.)

SUSTAINABILITY

Recycling Program

NOTES







Dia. = 1.81" (46mm) MOL = 9.75" (248mm) LCL = 5.75" (146mm) Base = Mogul(E39)

MH400/T15/HOR/4K

GENERAL Characteristics

| Lamp Type | Standard MH Single Ended | Lamp Watts |
|--------------------|--------------------------|---------------|
| ANSI Code | M59/E | Lamp Oper. \ |
| Bulb Shape | T15 | |
| Base Type | Mogul (E39) | SUSTAIN |
| Bulb Finish | Clear | Recycling Pro |
| Rated Life | 15000 hours | |
| Operating Position | Horizontal ± 15° | |


PHOTOMETRIC

| Initial Lumens | 36000 | |
|---|------------------------|--|
| Lumens Per Watt | 90 | |
| Scotopic Lumens (S/P 1.7) | 61200 | |
| Lamp Lumen Depreciation (LLD) | .65 (65%) @ 6000 hours | |
| Correlated Color Temperature | 4200K | |
| Chromaticity Coordinates (CIE-x,y).380 .377 | | |
| Color Rendering Index (CRI) | 65 | |
| | | |

PHYSICAL

| Bulb Diameter | 1.81" (46mm) |
|----------------------------|----------------|
| Max. Overall Length (MOL) | 9.75" (248mm) |
| Light Center Length (LCL) | 5.75" (146mm) |
| Effective Arc Length | 39 mm |
| Max. Base Temperature (°C) | 210 |
| Max. Bulb Temperature (°C) | 480 |
| Socket Pulse Rating (KV) | - |
| Luminaire Type | Enclosed Rated |

Spectral Distribution 4200K 80 Relative Energy 300 350 400 450 500 550 600 650 700 750 800 Wavelength (nm)



THIS LAMP CONFORMS TO FEDERAL STANDARD 21 CFR 1040.30

Warning: This lamp can cause skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when outer envelope is broken or punctured are commercially available.