LED Series

LED Dome Bollard with Cone Reflector



BOR3

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Reflector:

Aluminum Cone Reflector

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

Xicato LED Module:

Luminous Flux: 700lm @ 500mA (66 lpw),

550lm @ 350mA (77 lpw) CRI: ≥80, CCT: 4000K

Operating Temperature: -40°C to 80°C (@ Tc)

50,000 Hours

Module has IP66 Rating

RoHS Compliant

1x2 MacAdam Ellipse Color Specification

Wattage:

LED: 2 x 7.5 or 15w, 3 x 7.5w

Listing & Ratings:

CSA: Listed for Wet Locations

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths Upon Request.

LED Dome Bollard with Cone Reflector

Catalog #


Description

Complete Units
Ordering Information

Example: BOR3X3X7HU4W

BOR3	Model:	BOR3	
X	LED Mfr:	X=Xicato	
3X	Number of Modules:	2X=Two, 3X=Three	
7H	Wattage:	7H=7.5w, 15=15w* *15w Not Available for 3 Module Units.	
U	Ballast:	U=120-277V, 347=347V, 480=480V	
4	Color Temp:	4=4000K	
W	Color:	Z=Bronze, W=White, B=Black	
	Mounting:	N/A	
	Options:	N/A	

DIMENSIONS



BOR3


Catalog #	Description	
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts	
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts	
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts	
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts	
BOLPC	Replacement Polycarbonate Lens	

LED Series

LED Dome Bollard with Cone Reflector



BOLAN



BOLPC