



# BTH400GPSQ



JOB NAME: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

## DESCRIPTION

Metal Halide HID with temporary guard.

## SPECIFICATIONS

### UL Listing

Suitable for damp locations

### Housing

Die cast aluminum painted white. 3' cord and hook/loop. Heavy-duty sheet metal wiring box with 1/2 knockouts and easy leveling adjustment

### Ballast

Quad-Tap CWA Ballast (120/208/240/277 Volt)

### Watts

400 Watt

### Mounting Box

Die-cast aluminum mounting box tapped for 3/4" conduit

### Lamp

Mogul Base Up BT37 Metal Halide lamp supplied

### 2005 NEC Compliance

Open rated lamp and socket comply with 2005 NEC code

### Patents

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

### Color

-

### Weight

21.15

## ORDERING INFORMATION

Metal Halide Lamp supplied with fixture	Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
					120V	208V	240V	277V				
	400	BT37	Mogul Base Up	CWA-HPF QT	4	2.3	2	1.7	458.0	M155/O41000	20000	

**Factory Installed Options**  
Add suffix to Catalog Number

Note: Specifications may change without notice