
DLED6R8YY

LED retrofit downlights are perfect for updating existing recessed

lighting without changing the fixture. Equivalent to 50W Par.

Color: White



Weight: 0.0 lbs

LED Info Driver Info

Watts:	8W	Type:	Constant Current
Color Temp:	2700K	120V:	A80.0
Color Accuracy:	84	208V:	N/A
L70 Lifespan:	100000	240V:	N/A
LM79 Lumens:	539	277V:	N/A
Efficacy:	63 LPW	Input Watts:	9W
		Efficiency:	93%

Technical Specifications

UL Listed:

Suitable for damp locations.

Compatibility:

Low-profile design for maximum compatibility with many 5" and 6" incandescent recessed downlight housings. See housing compatibility.

Lumen Maintenance:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

LEDs:

High-output, long-life LEDs with 3 step binnning and integrated driver technology.

Driver:

Innovative integrated driver technology with 120V TRIAC and ELV dimming. See compatibility guide .

Spacing Criteria:

0-180° (along): 1.12.

Lens:

Polycarbonate diffusion lens for smooth light output.

Surge Protection:

2.5kv.

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

Housing:

Professional-grade, die-cast aluminum construction.

Edison E26 medium base adapter included. GU24 socket adapter sold separately.

Installation:

Pre-installed Torsion springs and optional friction clips are both included to aid in attaching and securing the 6" DLED to the incandescent housing.

Correlated Color Temp. (Nominal CCT):

2700K Residential Warm.

Fixture Efficacy:

63 Lumens per Watt.

Color Accuracy (CRI):

84 CRI.

Equivalency:

8W replaces 50W Par.

Finish:

Chip and fade resistant polyester powder coat finish.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

California Title 24:

DLED Retrofit Downlight complies with California Title 24 building and electrical codes.

Green Technology:

Mercury and UV free, and RoHS compliant.

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. See our full warranty.

Page 1 of 1



Email: sales@rabweb.com On the web at: www.rabweb.com Note: Specifications are subject to change without notice