
# FFLED18DC

LED Floodlights for solar applications or other 10-30 VDC systems. Perfect for off-grid, remote-area lighting. Up to 85% more efficient than line voltage AC solutions. Available in 10, 13 and 18 Watt Bullet, Spot and Rectangular shaped LED floods.

#### **LED Info Driver Info** DC to DC Watts: 18W Type: 120V: Color Temp: 5100K (Cool) N/A Color Accuracy: 70 208V: 0 L70 Lifespan: 100000 240V: N/A LM79 Lumens: 1,624 277\/· N/A Efficacy: 68 LPW Input Watts: 24W Efficiency: 75%



Color: Bronze



Weight: 4.8 lbs

# **Technical Specifications**

#### **Lumen Maintenance:**

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

#### LEDs:

Multi-chip 18 watt, high-output, long-life LEDs

#### **Electrical Input Specifications:**

Max Watts = 24W. Input Volts = 10-30 VDC. Operating Amps = 3.0 - 1.0A

## **Cold Weather Starting:**

The minimum starting temperature is -30°C (-22° F).

### **Thermal Management:**

Die-cast aluminum Thermal Management system for optimal heat dissipation

#### Housing:

Die-cast aluminum housing, hood and mounting arm

#### **NEMA Type:**

7H x 6V Beam Spread

#### **Input Watts:**

24W

#### **Fixture Efficacy:**

73 Lumens per Watt

#### **Mounting:**

Heavy-duty arm with "O" ring seal and stainless steel screws

#### **Color Stability:**

RAB LEDs exceed industry standards for chromatic stability

# **Color Accuracy:**

70 CRI

## **Color Temperature:**

5100K

#### **Color Uniformity:**

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2008.

#### Reflector:

Specular aluminum.

#### Gaskets:

High-temperature silicone gaskets

#### Finish:

Chip and fade resistant polyester powder coat finish

#### **Green Technology:**

Mercury and UV Free, and RoHS compliant

# IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

# California Title 24:

LFLOOD complies with California Title 24 building and electrical codes.

#### Patents:

The design of the LFLOOD is protected by US patents pending in US., Canada, China, Taiwan & Mexico.

Page 1 of 2



Email: sales@rabweb.com

On the web at: www.rabweb.com

Note: Specifications are subject to change without notice

FFLED18DC - continued

# Warranty:

RAB LED fixtures give you peace of mind because both the fixture and driver components are backed by RAB's 5 Year Warranty. For more information,

