

# RAB LIGHTING GT500R



JOB NAME: \_\_\_\_\_  
DATE: \_\_\_\_\_  
TYPE: \_\_\_\_\_

## DESCRIPTION

Gotcha Sensor with two weatherproof, corrosionproof floodlights, molded gaskets and corrosionproof universal cover plate. Lamps not supplied.

## SPECIFICATIONS

### UL Listing

Suitable for wet locations.

### Voltage

120 volts AC 60 Hz.

### Power Consumption

1 watt

### Time Adjustment

10 seconds to 5 minutes

### Surge Protection

Withstands up to 6000 volts

### Photoelectric Control

Deactivates lights during daylight

### Detector Sensitivity

Adjustable from 100% to 50%

### Wall Switch Manual Override

Two flip logic prevents activation by momentary power outages. Override resets to auto after 6 hours or at dawn. No extra wiring needed.

### Sensor Housing

Made of tough, corrosion resistant polycarbonate

### Floodlights

Made of tough, corrosion-resistant polycarbonate. For extra or replacement floodlights, order cat# TUFFY in your choice of color. Accepts PAR-38 lamps, medium base, 150 watts max. Lamps not included.

### Detection

110° view

### Patents


RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

**Weight**  
1.95


### Color

Black

## DIMENSIONS



## DETECTION PATTERN



Note: Specifications may change without notice

**RAB Lighting, Inc.** • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com  
© 2011