



LU300



JOB NAME: _____

DATE: _____

TYPE: _____

DESCRIPTION

Luminator sensor with two weatherproof, corrosionproof floodlights and round mounting plate. PRE-WIRED FOR EASY INSTALLATION. Both floods and sensor have universal ball swivels for easy tool-less adjustment. Lamps not supplied.

SPECIFICATIONS

UL Listing

Suitable for wet locations.

Voltage

120 volts AC 60 Hz.

Power Consumption

1 watt

Time Adjustment

8 seconds to 10 minutes

Photo Control

Deactivates lights during daylight

Detector Sensitivity

Adjustable from 100% to 50%

Wall Switch Manual Override

Two flip logic prevents activation by momentary power outages. Override resets to auto after 6 hours or at dawn. No extra wiring needed.

Auto Test Logic

5 minutes of test time when power is turned on, Rests to auto mode without further adjustment

Sensor Housing

Made of tough, corrosion resistant polycarbonate

Floodlights

Made of tough, corrosion-resistant polycarbonate. Accepts PAR-38 lamps, medium base, 150 watts max. Lamps not included.

Surge Protection

Withstands up to 3000 volts

Detection

110° view

Switching Capacity

300 watts incandescent @ 120 volts, 2.5 amps

Patents

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws.

Color

Bronze

Weight

1.24

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com

© 2011