


# SK9RYNW

Low-maintenance, high-efficiency LED retrofit fixture installs on standard junction boxes.

Color: White

Weight: 1.0 lbs



## LED Info

Watts: 9W  
 Color Temp: 3500K  
 Color Accuracy: 87  
 L70 Lifespan: 100000  
 LM79 Lumens: 744  
 Efficacy: 82 LPW

## Driver Info

Type: Constant Current  
 120V: 0.08A  
 208V: N/A  
 240V: N/A  
 277V: N/A  
 Input Watts: 9W  
 Efficiency: 99%

## Technical Specifications

### UL Listing:

Suitable for damp locations. Recommended for indoor use only.

### ENERGY STAR:

This product is ENERGY STAR® qualified.

### LEDs:

120V long-life LEDs with integrated driver technology and TRIAC and ELV dimming down to 5%. Power Factor 99.3%, 3 kV surge protection

### THD:

13.9% at 120V

### Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

### Housing:

Precision die-cast aluminum construction

### Mounting:

Simple slide-n-lock mounting bracket mounts to 3 1/2" and 4" round or octagon boxes with mounting screws 2 3/4" and 3 1/2" on center

### Lens:

Vandal resistant polycarbonate diffusion lens

### Equivalency:

SKEET 9W LED is equivalent to 60W incandescent, replaces up to 100W incandescent

### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contain no VOC or toxic heavy metals.

### Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

### Color Stability:

LED color temperature is warranted to shift no more than 200K in CCT over a 5 year period.

### Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.

### Green Technology:

Mercury and UV free, and RoHS compliant. Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

### California Title 24:

SK9RYNW complies with 2013 California Title 24 building and electrical codes as a commercial indoor fixture for general spaces when used with a vacancy sensor and compatible TRIAC or ELV dimming control. Select a vacancy sensor using catalog number LVS800. Dimming control provided by others.

### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.