

SQB1A

Mini Sensor and 75w or double 75w quartz bullet floods. Quartz Bullet has silicone O-ring gasket, thick tempered glass lens, internal and external cooling fins. Gold plated socket contacts and 250°C Teflon coated wires for extended lamp life. Lamp supplied.

Color: Bronze

Weight: 2.1 bs



Technical Specifications

UL Listing:

Suitable for wet locations.

Lamp:

75W T4 Bipin Lamp included.

Socket:

GY8

Switching Capacity:

500 watts Incandescent or 100 watts Fluorescent at 120 volts.

Voltage:

120 volts AC, 60Hz

Detection Zone:

Full 180 degrees by 30'.

Quick Test Time:

5 seconds test time for fast installation. Works day or night.

"No Hands" Auto Testing:

Auto mode starts after 4 minutes of testing. No adjustment needed

Time Adjustment:

5 seconds to 15 minutes.

Vandal Resistant Lens:

Hard lens resists vandalism.

Surge Protection:

Withstands up to 3000 volts.

Case Construction:

Precision molded Lexan

Photoelectric Control:

Deactivates lights during daylight. Fully adjustable for 24 hour operation or custom applications.

Manually Override:

Double flip wall switch logic prevents activation by short power outages. Resets after 8 hours. No extra wiring needed.

Built for Severe Conditions:

Double weatherproofing for long life.

LED Detection Indicator:

Glows red day and night for "on-guard" deterrence.

RF Immunity:

Circuits fully shielded for maximum radio frequency immunity.

Patents:

RAB sensor fixture designs are protected under U.S. and international intellectual property laws.