

DESCRIPTION

CATALOG: E-724-U-226-M1-S	BALLAST TYPE: Electronic	STARTING METHOD: Programmed Rapid Start	NUMBER OF LAMPS - LAMP TYPE: (2) F26W, (1) F26W, (1) F42W, (1) F32W Triple or Quad T4, (2) F24/27W Long Twin Tube T5, (2) F21, (1) F28, (1) F38W 2D T5 (1) FC9 22W, (1) FC12 40W Circline T5
-------------------------------------	------------------------------------	---	---

ELECTRICAL CHARACTERISTICS

INPUT VOLTAGE: 120 – 277 V~ +/- 10%	LAMP WATTS: 26/42/32/24/21 28/38/22/40W	INPUT WATTS: 25 to 55 W	INPUT CURRENT: 0,255 – 0,55 A	OCV: 425 V~ Min	PF: > 0,98	FREQUENCY: 50 / 60 Hz	SOUND RATED: A
MIN START TEMP: 32°F / 0°C	CLASS: P	TYPE: 1 outdoor	BALLAST FACTOR: 85%	BEF: 1.54	LAMP CONNECTION: Series	THD (1): < 10 %	NO PCB'S

(1) FOR 2-F26T4

PHYSICAL CHARACTERISTICS

	CASE DIMENSIONS						
	UNITS	M1	M2	M3	W	L	H
	INCHES	N/A	N/A	4,185	2.425	4.925	1,050
	TOL(+/-)	N/A	N/A	0,0125	0,0125	0,0125	0,0125
	MM	N/A	N/A	106,29	61.59	125.09	26.67
	TOL(+/-)	N/A	N/A	0,317	0,317	0,317	0,317
LEAD LENGTH							
UNITS	BLACK	WHITE	RED	BLUE	BLUE		
INCHES	N/A	N/A	N/A	N/A	N/A		
TOL(+/-)	N/A	N/A	N/A	N/A	N/A		
MM	N/A	N/A	N/A	N/A	N/A		
TOL(+/-)	N/A	N/A	N/A	N/A	N/A		

CARTON CHARACTERISTICS

UNITS/CARTON 10	CARTONS/LAYER 22	# OF LAYERS 10	UNITS/PALLET 2200	PIECE WEIGHT 0,41lb	CARTON WEIGHT 4.38 lb	PALLET WEIGHT 1014 lb
CARTONS/PALLET 220	CARTON DIMENSIONS 5.31" x 13.58" x 2.55"		PALLET DIMENSIONS 40" x 48" x 5.9"		PALLET DIMENSIONS LOADED, INCLUDING WOOD PALLET 40"X48"x 35.43"	

MISC.

--

CARTON LABEL

ISB SOLA BASIC

CAT. E-724-U-226-M1-S 120/277 V
0.550/0.255 A

(2) F26W, (1) F26W, (1) F42W,
(1) F32W Triple or Quad T4
(2) F24/27W Long Twin Tube T5
(2) F21, (1) F28, (1) F38W 2D T5
(1) FC9 22W, (1) FC12 40W Circline T5

**PROGRAMMED RAPID START
ELECTRONIC BALLAST**

10 UNITS

UL LISTED 5P49 **MADE IN MEXICO**

PRODUCT LABEL

SOLA

**PROGRAMMED RAPID START ELECTRONIC BALLAST
E-724-U-226-M1-S**

HIGH POWER FACTOR

INPUT VOLTAGE: 120/277V~ +/- 10%
INPUT CURRENT: 0.550/0.255 A
OCV: 425V~

INPUT WATTS: 25 to 55 W
INPUT CURRENT: 0.255 to 0.55 A

UNITS: (2) F26W, (1) F26W, (1) F42W,
(1) F32W Triple or Quad T4,
(2) F24/27W Long Twin Tube T5,
(2) F21, (1) F28, (1) F38W 2D T5
(1) FC9 22W, (1) FC12 40W Circline T5

INHERENT THERMAL PROTECTION NO PCB'S


ONLY USE RAPID START SOCKETS TO GROUND BALLAST CASE. INSTALL IN ACCORDANCE WITH NATIONAL AND LOCAL ELECTRICAL CODES. USE ONLY WITH AN ELECTRICAL ENCLOSURE.

CAUTION: VOLTAGE OVERLOAD! SOLID RATED EQL PROTECTION. MINIMUM AMBIENT TEMPERATURE 0°C (32°F).

5 YEAR WARRANTY

TYPE 1 OUTDOOR CLASS P

ELECTRICAL DIAGRAM



ISB LIGHTING & POWER SOURCE

2840 KELLER SPRINGS ROAD,
SUITES 1102 AND 1103
CARROLLTON, TX. 75006
U.S.A.
Tel. 972-416-4500
Fax. 972-418-5858

Data is based upon tests performed by Industrias Sola Basic in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Made in Mexico by Industrias Sola Basic S.A. de C.V.