

[Return to search](#)[Print Page](#)

Product Number: 25150
Order Abbreviation: F48T12/D/HO
General Description: 60W, 48" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI

Product Information

Abbrev. With Packaging Info.	F48T12DHO 30/CS 1/SKU
Actual Length (in)	46
Actual Length (mm)	1168.4
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.59
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	3600
Mean Lumens at 25C	2916
Nominal Length (in)	48
Nominal Wattage (W)	60.00

Additional Product Information

[Product Documents, Graphs, and Images](#)

[Compatible Ballast](#)

[Packaging Information](#)



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.

[Print Page](#)

