

Product 25270

Number:

Order F72T12/D/VHO

Abbreviation:

General 160W, 72"MOL, T12 VHO (1500 mA) rapid start fluorescent **Description:** lamp, Daylight phosphor, 6500K color temperature, 76 CRI

Product Information		
Abbrev. With Packaging Info.	F72T12DVHO 15/CS 1/SKU	
Actual Length (in)	69.909	
Actual Length (mm)	1775.69	
Average Rated Life (hr)	10000	
Base	Recessed Double Contact	
Bulb	T12	
Color Rendering Index (CRI)	76	
Color Temperature/CCT (K)	6500	
Diameter (in)	1.590	
Diameter (mm)	40.46	
Family Brand Name	VHO	
Industry Standards	ANSI C78.81 - 2001	
Initial Lumens at 25C	9400	
Mean Lumens at 25C	6580	
Mean Lumens at 35C	6580	
Nominal Length (in)	72.000	
Nominal Length (mm)	1828.80	
Nominal Wattage (W)	160.00	



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 15,000 hours.

1 of 1 8/26/2010 2:56 PM