

[Return to search](#)[Print Page](#)**Product Number:** 25343**Order Abbreviation:** F42T12/D/HO**General Description:** 55W, 42" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Daylight phosphor, 6500K color temperature, 76 CRI**Product Information**

Abbrev. With Packaging Info.	F42T12DHO 30/CS 1/SKU
Actual Length (in)	39.91
Actual Length (mm)	1013.7
Average Rated Life (hr)	9000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	76
Color Temperature/CCT (K)	6500
Diameter (in)	1.59
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	3050
Mean Lumens at 25C	2471
Nominal Length (in)	42
Nominal Wattage (W)	55.00

Additional Product Information[Product Documents, Graphs, and Images](#)[Packaging Information](#)**Footnotes**

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.

[Print Page](#)

