



Product Number: 50707

Order Abbreviation: QTP 2X32T8/UNV DIM-TC

General Description: 2-lamp universal voltage electronic dimming ballast for 32W T8 lamp

Product Information

Abbrev. With Packaging Info.	QTP2X32T8UNVDIMTC
Ballast Factor	0.88
Ballast Height H (in)	1.0000
Ballast Length L (in)	9.5000
Ballast Width W (in)	1.6810
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120.00
Nominal Voltage (V)	120-277V
Number of Lamps	2
Open Circuit Voltage (V)	<600V
Power Factor	>0.95
Primary Lamp Type	FO32/XP
Sound Rating	A
Starting Method	PROStart
Starting Temperature - Fahrenheit	50
Starting Temperature - Celsius	10
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads
Total Maximum Wattage	64



QUICK 60+™
ELECTRONIC BALLAST

Footnotes

- Dimming Range 100-5%
- UL Listed Class P, Type 1 Outdoor
- Insulate unused leads
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Input Frequency: 50/60Hz.
- Minimum Starting Temperature: 50F/10C.
- Data shown is at full light output.
- Remote mounting up to 8 feet.