



Product Number: 56007

Order Abbreviation: aluPAR 64/NSP/500W/120V

General Description: PAR64, 500 watt, 120 volt, halogen, GX16D, NSP

| Product Information | |
|------------------------------|--------------------------------|
| Abbrev. With Packaging Info. | ALUPAR64NSP500W120V 6/CS 1/SKU |
| Application | STAGE & STUDIO, ARCHITECTURAL |
| Average Rated Life (hr) | 2000 |
| Base | External Mogul End Prong GX16D |
| Beam Angle (deg) | 11 X 9 |
| Beam Type | NSP |
| Bulb | PAR64 |
| Centerbeam Candlepower (cp) | 116000 |
| Color Rendering Index (CRI) | 100 |
| Color Temperature (K) | 2950 |
| Diameter d (in) | 8.031 |
| Diameter d (mm) | 204.00 |
| Family Brand Name | aluPAR |
| Length l (in) | 5.75 |
| Length l (mm) | 146 |
| Luminous Flux (lm) | 11000 |
| Nominal Voltage (V) | 120.00 |
| Nominal Wattage (W) | 500.00 |
| Operating Position | ANY |
| Reflector Coating | 204.00 |



Footnotes

- NSP=Narrow Spot
- Easy disassembly into components allow for environmentally preferred waste disposal
- Aluminum reflector reduces weight by up to 50% compared to standard glass PAR lamps