

[Return to search](#)[Print Page](#)

Product Number: 64468
Order Abbreviation: M1000/U
General Description: 1,000W general lighting metal halide lamp, universal burn, clear

Product Information

Abbrev. With Packaging Info.	M1000U 6/CS 1/SKU
ANSI Code	M47/S
Approx. Lumens (initial - horizontal)	107800
Approx. Lumens (initial - vertical)	110000
Approx. Lumens (mean - horizontal)	86000
Approx. Lumens (mean - vertical)	86000
Arc Length (in)	3.58
Arc Length (mm)	91
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Average Rated Life - Vertical (hr)	18000
Base	E39 Mogul
Bulb	BT56
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Diameter (in)	7
Diameter (mm)	178
Family Brand Name	Metalarc®
Fixture Requirement	S
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	9.5
Light Center Length - LCL (mm)	241
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	15.4
Maximum Overall Length - MOL (mm)	391
Nominal Voltage (V)	263.00

Nominal Wattage (W)	1000.00
Operating Position	Universal
Warm-up Time (min)	2-4

Additional Product Information[Product Documents, Graphs, and Images](#)[Compatible Ballast](#)[Packaging Information](#)**Footnotes**

- S = When operated within 15 degrees of vertical, this lamp may be operated in an open luminaire provided the installation is not near people or flammable or combustible material, otherwise it must be operated in a suitably enclosed luminaire. See lamp warning.

[Print Page](#)