

[Return to search](#)[Print Page](#)

Product Number: 64489

Order Abbreviation: M400/C/U/BT28

General Description: 400W METALARC compact quartz metal halide lamp, reduced outer jacket, E39 base, BT28 bulb, enclosed fixture rated, universal burn, coated, 3600K

Product Information

| | |
|---------------------------------------|-----------------------|
| Abbrev. With Packaging Info. | M400CUBT28 6/CS 1/SKU |
| ANSI Code | M59/E |
| Approx. Lumens (initial - horizontal) | 32000 |
| Approx. Lumens (initial - vertical) | 36000 |
| Approx. Lumens (mean - horizontal) | 20500 |
| Approx. Lumens (mean - vertical) | 22500 |
| Average Rated Life - Horizontal (hr) | 15000 |
| Average Rated Life - (hr) | 15000 |
| Average Rated Life - Vertical (hr) | 20000 |
| Base | E39 Mogul |
| Bulb | BT28 |
| Color Rendering Index (CRI) | 70 |
| Color Temperature/CCT (K) | 3600 |
| Diameter (in) | 3.5 |
| Diameter (mm) | 89 |
| Family Brand Name | Compact Metalarc® |
| Fixture Requirement | E |
| Hot Restrike Time (min) | 7-12 |
| Lamp Finish | Coated |
| Light Center Length - LCL (in) | 5 |
| Light Center Length - LCL (mm) | 127 |
| Maximum Base Temperature - Fahrenheit | 482 |
| Maximum Base Temperature - Celsius | 250 |
| Maximum Bulb Temperature - Fahrenheit | 752 |
| Maximum Bulb Temperature - Celsius | 400 |
| Maximum Overall Length - MOL (in) | 8.31 |
| Maximum Overall Length - MOL (mm) | 211 |
| Nominal Voltage (V) | 135.00 |
| Nominal Wattage (W) | 400.00 |
| Operating Position | Universal |

| | |
|--------------------|-----|
| Warm-up Time (min) | 2-4 |
|--------------------|-----|

Additional Product Information**Product Documents, Graphs, and Images****Compatible Ballast****Packaging Information****Footnotes**

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.

[Print Page](#)