

[Return to search](#)[Print Page](#)

Product Number: 64714
Order Abbreviation: MP1000/BU-ONLY
General Description: 1000W METALARC PRO-TECH quartz metal halide lamp, EX39 base, BT56 bulb, open fixture rated, base up only, clear, 3600K

Product Information

Abbrev. With Packaging Info.	MP1000BUONLY 6/CS 1/SKU
ANSI Code	M47/O
Approx. Lumens (initial - vertical)	109000
Approx. Lumens (mean - vertical)	87500
Arc Length (in)	3.58
Arc Length (mm)	91
Average Rated Life - Vertical (hr)	15000
Base	EX39 Exclusionary Mogul
Bulb	BT56
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	3500
Diameter (in)	7
Diameter (mm)	178
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	0
Hot Restrike Time (min)	10
Lamp Finish	Clear
Light Center Length - LCL (in)	9.5
Light Center Length - LCL (mm)	241
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	15.4
Maximum Overall Length - MOL (mm)	391
Nominal Voltage (V)	263.00
Nominal Wattage (W)	1000.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Additional Product Information**[Product Documents, Graphs, and Images](#)****[Packaging Information](#)****Footnotes**

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.

[Print Page](#)