



Product Number: 64716

Order Abbreviation: MP1000/C/BU-ONLY

General Description: 1000W METALARC PRO-TECH quartz metal halide lamp, EX39 base, BT56 bulb, open fixture rated, base up only, coated, 3400K

Product Information

| | |
|---------------------------------------|---------------------------|
| Abbrev. With Packaging Info. | MP1000CBUONLY 6/CS 1/SKU |
| ANSI Code | M47/O |
| Approx. Lumens (initial - vertical) | 102000 |
| Approx. Lumens (mean - vertical) | 82000 |
| Average Rated Life - Vertical (hr) | 15000 |
| Base | EX39 Exclusionary Mogul |
| Bulb | BT56 |
| Color Rendering Index (CRI) | 70 |
| Color Temperature/CCT (K) | 3200 |
| Diameter (in) | 7.000 |
| Diameter (mm) | 178.00 |
| Family Brand Name | Metalarc Pro-Tech® |
| Fixture Requirement | O |
| Hot Restrike Time (min) | 10 |
| Lamp Finish | Coated |
| Light Center Length - LCL (in) | 9.5 |
| Light Center Length - LCL (mm) | 241 |
| Maximum Base Temperature - Fahrenheit | 410 |
| Maximum Base Temperature - Celsius | 210 |
| Maximum Bulb Temperature - Fahrenheit | 752 |
| Maximum Bulb Temperature - Celsius | 400 |
| Maximum Overall Length - MOL (in) | 15.4 |
| Maximum Overall Length - MOL (mm) | 391 |
| Nominal Voltage (V) | 263.00 |
| Nominal Wattage (W) | 1000.00 |
| Operating Position | Base up within 15deg only |
| Warm-up Time (min) | 2-4 |

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.