



Product Number: 64896

Order Abbreviation: MCP39PAR20/U/940/FL

General Description: Ceramic MH 39W PAR20 Flood, 4000K

Product Information

| | |
|---------------------------------------|------------------------------|
| Abbrev. With Packaging Info. | MCP39PAR20U940FL 12/CA 1/SKU |
| ANSI Code | C130/O |
| ANSI Code 2 | C130/O |
| Approx. Lumens (initial - horizontal) | 1850 |
| Average Rated Life - Horizontal (hr) | 12000 |
| Average Rated Life - (hr) | 12000 |
| Average Rated Life - Vertical (hr) | 12000 |
| Avg Rated Life (hrs) | 12000 |
| Base | E26 Medium |
| Bulb | PAR20 |
| Centerbeam Candlepower (cp) | 4000 |
| Color Rendering Index (CRI) | 90 |
| Color Temperature/CCT (K) | 3900 |
| Diameter (in) | 0.000 |
| Diameter (mm) | 0.00 |
| Family Brand Name | POWERBALL |
| Fixture Requirement | O |
| Hot Restrike Time (min) | 4-6 |
| Lamp Finish | Clear |
| Maximum Base Temperature - Fahrenheit | 410 |
| Maximum Base Temperature - Celsius | 210 |
| Maximum Bulb Temperature - Fahrenheit | 572 |
| Maximum Bulb Temperature - Celsius | 300 |
| Maximum Overall Length - MOL (in) | 3.65 |
| Maximum Overall Length - MOL (mm) | 92.7 |
| Nominal Voltage (V) | 90.00 |
| Nominal Wattage (W) | 39.00 |
| Warm-up Time (min) | 2-4 |

Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- UV-Stop quartz