



Product Number: 64898

Order Abbreviation: MCP39PAR30LN/U/940/FL/ECO

General Description: Ceramic MH 39W PAR30Long Neck, 4000K

Product Information

Abbrev. With Packaging Info.	MCP39PAR30LNU940FLECO 6/CS 1/SKU
ANSI Code	C130/O
ANSI Code 2	C130/O
Approx. Lumens (initial - horizontal)	2200
Approx. Lumens (initial - vertical)	2200
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Average Rated Life - Vertical (hr)	12000
Avg Rated Life (hrs)	12000
Base	E26 Medium
Bulb	PAR30LN
Centerbeam Candlepower (cp)	7500
Color Rendering Index (CRI)	90
Color Temperature/CCT (K)	4000
Diameter (in)	0.000
Diameter (mm)	0.00
Family Brand Name	POWERBALL
Fixture Requirement	O
Hot Restrike Time (min)	4-6
Lamp Finish	Clear
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	572
Maximum Bulb Temperature - Celsius	300
Maximum Overall Length - MOL (in)	4.76
Maximum Overall Length - MOL (mm)	121
Nominal Voltage (V)	95.00
Nominal Wattage (W)	39.00

Operating Position	Universal
Warm-up Time (min)	2-4

Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- UV-Stop quartz