

[Return to search](#)[Print Page](#)

**Product Number:** 67506  
**Order Abbreviation:** LU100/MED  
**General Description:** 100W LUMALUX high pressure sodium HID lamp, E26 based, E17 bulb, universal burn, clear, 2100K

#### Product Information

Abbrev. With Packaging Info.	LU100MED 20/CS 1/SKU
ANSI Code	S54
Approx. Lumens (initial - horizontal)	9500
Approx. Lumens (initial - vertical)	9500
Approx. Lumens (mean - horizontal)	8000
Approx. Lumens (mean - vertical)	8000
Arc Length (in)	1.12
Arc Length (mm)	28.4
Average Rated Life - Horizontal (hr)	24000
Average Rated Life - (hr)	24000
Avg Rated Life (hrs)	24000+
Base	E26 Medium
Bulb	E17
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.13
Diameter (mm)	54
Family Brand Name	Lumalux®
Fixture Requirement	O
Hot Restrike Time (min)	1 MIN
Lamp Finish	Clear
Light Center Length - LCL (in)	3.42
Light Center Length - LCL (mm)	86.87
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	5.43
Maximum Overall Length - MOL (mm)	138

Nominal Voltage (V)	55.00
Nominal Wattage (W)	100.00
Operating Position	Universal
Warm-up Time (min)	3-4 MINUTES

**Additional Product Information****Product Documents, Graphs, and Images****Compatible Ballast****Packaging Information****Footnotes**

- Use with 4000V pulse rated sockets only.
- Mean lumens measured at 50% of average rated life

[Print Page](#)