



Product 64705

Number:

Order MP400/BU-TC

Abbreviation:

General 400W METALARC PRO-TECH quartz metal halide lamp,  
 Description: EX39 base, BT37 bulb, open fixture rated, base up only, clear,  
 3600K, tuff-coat

## Product Information

Abbrev. With Packaging Info.	MP400BUTC 6/CS 1/SKU
Approx. Lumens (initial - vertical)	40000
Approx. Lumens (mean - vertical)	26000
Arc Length (in)	1.77
Arc Length (mm)	45
Average Rated Life - Horizontal (hr)	20000
Average Rated Life - (hr)	20000
Average Rated Life - Vertical (hr)	20000
Base	EX39 Exclusionary Mogul
Bulb	BT37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	3600
Diameter (in)	4.606
Diameter (mm)	117.00
Family Brand Name	Metalarc Pro-Tech®
Fixture Requirement	O
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	410
Maximum Base Temperature - Celsius	210
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	135.00
Nominal Wattage (W)	400.00
Operating Position	Base up within 15deg only
Warm-up Time (min)	2-4

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning