



LED MR16s

DIMMABLE LED TECHNOLOGY

Superior Performance

- LIFE** 25,000 hours
- COLOR** Excellent color consistency, lamp to lamp
- BASE** Available in E26, GU10 and GU5.3 base
- UL LISTING** Approved for dry and damp locations
- DIMMING** Fully dimmable from 100% to 0.5%
(3 or more lamps recommended per circuit for optimum dimming)
- VOLTAGE** 120 Volt and 12 Volt
- WARRANTY** 3 Years
- DIMMER COMPATIBILITY** For up to date information on dimmer compatibility, visit www.tcpi.com



COMPARE AND SAVE

INCANDESCENT
35W MR16 vs. **7W LED MR16**

35 WATTS USED
3,000 HOUR LIFE
REPLACE IN 25 MONTHS

7 WATTS USED
25,000 HOUR LIFE
REPLACE IN 22 YEARS

LED REFLECTOR LAMPS DIMMABLE

Retail Item #	Description	Master Pack	Watts (ENERGY USED)	Incan. Equiv.	Lumens (LIGHT OUTPUT)	Life (HOURS)	MOL	DIA	Warranty (YEARS)	Color Temp.	Base Type	UPC	Energy Star
RLP166W30K	LED 6W PAR16 FLOOD - 3000K 40 DEGREE BEAM ANGLE	12	6	25	210	25,000	3.05	2.00	3	3000	E26	7-62148-22977-3	★
RLMR166GU1030K	LED 6W GU10 MR16 FLOOD - 3000K 40 DEGREE BEAM ANGLE	12	6	25	210	25,000	2.50	2.00	3	3000	GU10	7-62148-22978-0	
RLMR16612V30K	LED 6W 12 Volt MR16 FLOOD - 3000K	12	6	25	210	25,000	2.50	2.00	3	3000	GU5.3	7-62148-22979-7	★
RLP167W30KD	LED 7W PAR16 FLOOD - 3000K 40 DEGREE BEAM ANGLE	12	7	35	350	25,000	3.05	2.00	3	3000	E26	7-62148-23077-9	★
RLMR167GU1030KD	LED 7W GU10 MR16 FLOOD - 3000K 40 DEGREE BEAM ANGLE	12	7	35	350	25,000	2.50	2.00	3	3000	GU10	7-62148-23078-6	
RLMR16712V30KD	LED 7W 12V MR16 FLOOD - 3000K	12	7	35	350	25,000	2.00	2.00	3	3000	GU5.3	7-62148-23079-3	
RLP168W30KD	LED 8W PAR16 FLOOD - 3000K 40 DEGREE BEAM ANGLE	12	8	50	500	25,000	3.05	2.00	3	3000	E26	7-62148-25280-1	★
RLMR168GU1030KD	LED 8W GU10 MR16 FLOOD - 3000K 40 DEGREE BEAM ANGLE	12	8	50	500	25,000	2.50	2.00	3	3000	GU10	7-62148-25281-8	
RLMR16812V30KD	LED 8W 12V MR16 FLOOD - 3000K	12	8	50	500	25,000	2.00	2.00	3	3000	GU5.3	7-62148-25282-5	