

JC SERIES

- Only for Use in Approved Enclosed Halogen Fixtures
- Glass 2-Pin Base - G6.35, GY6.35

Watts	Ushio Ordering Code	Ushio Lamp Code	Dimensions			Filament Type	Approx Lumens lm	Color Temp K	Avg Life h	Burn Position	Bulb Finish	Case Qty	Fig No
			Dia (A)	MOL (B)	LCL (C)								
<b>Glass 2-Pin Base – G6.35</b>													
20	1000822	JC12V-20W	0.43	1.73	1.18	C-6	280	2850	2000	Univ	Clear	100	1
35	1000823	JC12V-35W	0.43	1.73	1.18	C-6	650	2900	2000	Univ	Clear	10	1
50	1000830	JC12V-50WG1.0	0.43	1.73	1.18	C-6	900	2900	2000	Univ	Clear	100	1
50	1000829	JC12V-50WF	0.41	1.73	1.18	C-6	840	3000	2000	Univ	Frosted	100	1
50	1000848	JC24V-50W	0.41	1.73	1.18	C-6	750	2950	2000	Univ	Clear	100	1
75	1000834	JC12V-75W	0.43	1.73	1.18	C-6	2200	3300	2000	Univ	Clear	100	1
100	1000839	JC24V-100W	0.43	1.73	1.18	CC-6	1800	3000	2000	Univ	Clear	10	1
<b>Glass 2-Pin Base – GY6.35</b>													
35	1000824	JC12V-35W	0.43	1.73	1.18	C-8	650	2900	2000	BD/Hor	Clear	10	2
35	1003486	JC12V-35WF	0.43	1.73	1.18	C-8	650	2900	2000	BD/Hor	Frosted	10	2
50	1000827	JC12V-50W	0.43	1.73	1.18	C-6	1000	3000	2000	Univ	Clear	10	3
50	1000828	JC12V-50W	0.43	1.73	1.18	C-8	1000	3000	2000	Univ	Clear	100	2
50	1003487	JC12V-50WF	0.43	1.73	1.18	C-8	1000	3000	2000	Univ	Frosted	10	2
75	1000835	JC12V-75W	0.43	1.73	1.18	C-6	1600	3000	2000	Univ	Clear	10	3
100	1000806	JC12V-100W	0.43	1.73	1.18	C-6	2300	3000	2000	Univ	Clear	10	3
100	1000807	JC12V-100WG	0.43	1.73	1.18	C-8	2300	3000	2000	Univ	Clear	10	2
100	1000381	EVA, JC12V-100H20	0.45	1.73	1.18	CBar6	2400	3000	2000	BD/Hor	Clear	10	3
100	1000490	FCR, JC12V-100W	0.43	1.65	1.18	CBar6	3000	3300	50	BD/Hor	Clear	10	3
100	1000507	FDX, JC12V-100WCG2	0.45	1.73	1.18	CBar6	3500	3300	50	Univ	Clear	12	4
300	1000545	FLW, JC24V-300WA-H	0.53	2.17	1.18	CBar6	10450	3500	50	BD	Clear	10	4
300	1000846	JC24V-300WB/GY6.35	0.69	2.17	0.91	CBar6	6600	3050	1000	Univ	Clear	10	3

All dimensions shown in inches unless otherwise noted.

